

Description

- RoHS Compliant
- Surface mount fuse, fast acting
- Rapid interruption of excessive current
- Compatible with reflow and wave solder
- Excellent environmental integrity
- Ampere rating marked and oriented facing up in carrier
- Solder-free design provides excellent temperature cycling characteristics
- Heat and shock tolerant

ELECTRICAL CHARACTERISTICS		
Ampere Rating	% of Amp Rating	Opening Time
250mA - 7A	100%	4 Hours Minimum
1.25A - 3A	200%	60 Seconds Maximum
250mA - 3A	250%	5 Second Maximum
4A - 7A	350%	1 Second Maximum

Agency Information


- UL Recognition Guide & File numbers:
JDYX2 & E19180.
- CSA Component Acceptance: 053787 C 000 &
Class No: 1422 30.

Environmental Data

- Thermal Shock: MIL-STD-202, Method 107,
Test Condition B
- Vibration: MIL-STD-202, Method 204, Test Condition C
- Moisture Resistance: MIL-STD-202, Method 106,
10 day cycle
- Solderability: ANSI/J-STD-002, Test B


Ordering

- Specify packaging code and product code
(i.e. TR/3216FF250-R)




Dimensions ^{mm/(inches)}

Drawing Not to Scale



Land Pattern



Soldering Method

- Wave Immersion: 260°C, 10 sec max.
- Infrared Reflow: 260°C, 30 sec max.

SPECIFICATIONS							
Product Code	Current Rating	Voltage Rating		Interrupting Rating* AC/DC	Resistance (ohms)** Typ.	Typical Melt I ² t† DC	Typical Voltage Drop (V)‡
		AC	DC				
3216FF250-R	250mA	32 V	63 V	50 A	3.50	0.000084	1.4
3216FF375-R	375mA	32 V	63 V	50 A	1.75	0.0002	0.73
3216FF500-R	500mA	32 V	63 V	50 A	0.98	0.0019	0.66
3216FF750-R	750mA	32 V	63 V	50 A	0.75	0.00095	0.63
3216FF1-R	1A	32 V	63 V	50 A	0.219	0.007	0.20
3216FF1.5-R	1.5A	32 V	63 V	50 A	0.119	0.029	0.18
3216FF2-R	2A	32 V	63 V	50 A	0.066	0.049	0.16
3216FF2.5-R	2.5A	32 V	63 V	50 A	0.046	0.112	0.14
3216FF3-R	3A	32 V	63 V	50 A	0.036	0.165	0.13
3216FF4-R	4A	32 V	32 V	50 A	0.018	0.189	0.11
3216FF4.5-R	4.5A	32 V	32 V	50 A	0.016	0.328	0.10
3216FF5-R	5A	32 V	32 V	50 A	0.014	0.619	0.09
3216FF6.5-R	6.5A	32 V	32 V	50 A	0.0085	3.21	0.076
3216FF7-R	7A	32 V	32 V	50 A	0.0085	3.53	0.078

* AC Interrupting Rating (Measured at rated voltage with a unity power factor); DC Interrupting Rating (Measured at rated voltage, time constant of less than 50 microseconds, battery source)

** DC Cold Resistance (Measured at 10% of rated current)


† Typical Melting I²t (Measured with a battery bank at rated DC voltage, 10x-rated current, not to exceed IR, time constant of calibrated circuit less than 50 microseconds) (6.5A & 7A measured at interrupting rating)

‡ Typical Voltage Drop (Measured at rated current after temperature stabilizes)

It is recommended that fuses be mounted with ceramic (white) side facing up.

Device designed to carry rated current for four hours minimum. An operating current of 80% or less of rated current is recommended, with further derating required at elevated ambient temperatures.

TIME CURRENT CURVE



PACKAGING CODE	
Packaging Code	Description
TR	3,000 pieces of fuses on 8mm tape-and-reel on a 7 inch (178mm) reel per EIA Standard 481

North America

Cooper Electronic Technologies
3601 Quantum Boulevard
Boynton Beach, FL 33426-8638
Tel: 1-561-752-5000
Fax: 1-561-742-0134
Toll Free: 1-888-414-2645

Cooper Bussmann
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-800-544-2570

Europe

Cooper Electronic Technologies
Cooper (UK) Limited
Burton-on-the-Wolds
Leicestershire • LE12 5TH UK
Tel: +44 (0) 1509 882 737
Fax: +44 (0) 1509 882 786

Asia Pacific

Cooper Electronic Technologies
1 Jalan Kilang Timor
#06-01 Pacific Tech Centre
Singapore 159303
Tel: +65 278 6151
Fax: +65 270 4160