



Earth Terminals Type EK Screw Clamp Connections




EK 16/35
87A




Thickness 12mm

EK 35/35
143A



Thickness 16mm

EK 16/35
87A



Thickness 8mm

Technical Data

Conductor size	Solid (mm ²)	2.5-16	6-16	2.5-16
	Stranded (mm ²)	4-16	6-35	4-16

Insulation stripping length	(mm)	12	20	12
-----------------------------	------	----	----	----

Ordering Data

Moulding material		Cat. No.	Cat. No.	Cat. No.
Polyamide		019016	066146	
(green/yellow)				
Mild steel				066040

Approvals



All Approvals are listed
in Approvals Section

Terminal Rail (2m)

	Type	Cat. No.	Type	Cat. No.	Type	Cat. No.
Steel 35 x 7.5mm	TS 35	038340	TS 35	038340	TS 35	038340
Steel 35 x 7.5mm (M6 Slots)	TS 35	067620	TS 35	067620	TS 35	067620
Steel 35 x 15mm	TS 35	049800	TS 35	049800	TS 35	049800

Rail Support Block

Melamine	SH 2	049492	SH 2	049492	SH 2	049492
----------	------	--------	------	--------	------	--------



Marking Tags

All marking systems are shown in Section 11	DEKAFIX – Section 11	DEKAFIX – Section 11	DEKAFIX – Section 11
---	----------------------	----------------------	----------------------

For additional accessories see Section 11