

Installation terminals

N-conductor disconnect terminals


These special modular terminals are specified for insulation measurements without disconnecting the conductor according to VDE standards for places of public assembly.

width x length x height with TS 35 x 7.5 mm
 max. current / max. cond. cross-section A/mm²
 max. clamping range mm²

WNT 2.5

2.5 mm²


5.1 x 60 x 47
32 / 4
0.13 ... 4



WNT 4

4 mm²

6.1 x 60 x 47
41 / 6
0.13 ... 6



Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Stripping length / Blade size	mm / -
Tightening torque range (clamping screw)	Nm
Note	

IEC 60947-7-1 / VDE 0611-4

IEC	UL	CSA	EN 60079-7
400	600	600	
24	25	20	
2.5	AWG 22... 12	AWG 26... 12	
6 / 3			
A3 / V-0			



Rated connection

0.5...4 / 1.5...4
 0.5...4 / 0.5...2.5
 10 / 0.6 x 3.5
 0.4...0.6 (M 2.5)

Tightening torque, N-disconnector 0.4...0.6 Nm

IEC 60947-7-1 / VDE 0611-4

IEC	UL	CSA	EN 60079-7
400	600	600	
32	35	35	
4	AWG 22... 10	AWG 26... 10	
6 / 3			
A4 / V-0			



Rated connection

0.5...6 / 1.5...6
 0.5...6 / 0.5...4
 10 / 0.6 x 3.5
 0.5...1.0 (M 3)

Tightening torque, N-disconnector 0.4...0.8 Nm

Ordering data

Version	
	dark beige Wemid
	blue Wemid
Note	

Type	Qty.	Order No.
WNT 2.5 10X3 BE	100	1010600000
WNT 2.5 10X3	100	1010680000
2.5 mm ² conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs)		

Type	Qty.	Order No.
WNT 4 10X3 BE	100	1010700000
WNT 4 10X3	100	1010780000

Accessories

Cross-connection	
	2-pole 3-pole 4-pole 10-pole 20-/24-pole
End plate / Partition plate	
	dark beige Wemid
	blue Wemid
Mounting plate for 10 x 3 (required every 200 mm)	
	blue Wemid for vertical installation position
End bracket	
	dark beige
Screwdrivers	
	with cutting device "swifty set"
	Standard
Busbar 10 x 3 (140A)	
	(further types in chapter F)
	top of busbar to top of TS 35 = 25.5 mm
Tension clamp for supplying 10 x 3 busbars	
	rigid / flexible 0.5 - 6 / 4mm ²
	rigid / flexible 6 - 16 / 4mm ²
	flexible 16 - 35mm ²
Marking systems	
	(see large assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications see "Accessories"	

Type	Current [A]	Qty.	Order No.
WAP 2.5-10	1.5	50	1050000000
WAP 2.5-10 BL	1.5	50	1050080000
width [mm]			
WHP 2.5-35N/10x3 BL	2	20	1050280000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
width [mm]			
SSCH 10X3X1000 CU/SN		1	0348900000
width [mm]			
ZB 4	5.6	50	0316500000
ZB 16 ZKSC	10	50	0316600000
ZB 35/M6X16	14	20	0266500000
width [mm]			
WS 12/5			

Type	Current [A]	Qty.	Order No.
WAP 2.5-10	1.5	50	1050000000
WAP 2.5-10 BL	1.5	50	1050080000
width [mm]			
WHP 2.5-35N/10x3 BL	2	20	1050280000
width [mm]			
WEW-35/2	8	100	1061200000
width [mm]			
SWIFTY SET		1	9006060000
SD 0.6x3.5x100		1	9008330000
width [mm]			
SSCH 10X3X1000 CU/SN		1	0348900000
width [mm]			
ZB 4	5.6	50	0316500000
ZB 16 ZKSC	10	50	0316600000
ZB 35/M6X16	14	20	0266500000
width [mm]			
WS 12/5			

