


9920-21-22-26, 2720-21 Max. 40 W

AC/DC SWITCH MODE POWER SUPPLIES



- 9920 - 3-pin IEC 320
- 9921 - 2-pin IEC 320
- 9922 - fixed mains cord / fast nettleledning
- 9926 - exchangeable AC plugs / utskiftbare
- 2720 - 2-pin IEC 320 tilfredsst. CEC-compliant / CEC std.
- 2721 - CEC with exch. / utskiftbare AC plugs

- Universal input voltage (90-264 VAC)
- Medically certified (EN 60601)
- UL-approved (99XX)
- Mounting bracket available
- Mains cord not included
- Universal inngangsspenning (90-264 VAC)
- Medisinsk sertifisert (EN 60601)
- UL-godkjent (99XX)
- Kan leveres med festebrakett
- Nettledning ikke inkludert



Technical specifications

Tekniske data

13,2 V*

Input voltage:	Inngangsspenning:	90-264 VAC
Line frequency:	Frekvensområde:	47-63 Hz
Min. output current:	Min. laststrøm:	0A
Load regulation:	Lastregulering:	< 1 %
Mains regulation:	Linjeregulering:	< 0,5%
Switch frequency approx.:	Svitsjefrekvens ca.:	40 kHz
Overshoot (90-10% load variation):	Oversving (90-10% lastvariasjon):	< 300 mV
Undershoot (10-90% load variation):	Undersving (10-90% lastvariasjon):	< 300 mV
Hold-up time:	Hold-up time:	> 20 ms
Temperature range	Temperaturområde	
• Operating:	• Drift:	-20 - +40°C
• With derating:	• Med derating:	+60°C
• Storage:	• Lagring:	-25 - +85°C
Derating:	Derating:	1W/°C over 40°C
Derating UL-version:	Derating UL-versjon:	TA from 30 to 40°C : 32W
Ripple:	Rippel:	50 mV p-p
Efficiency (at 100% load, 230 V):	Virkningsgrad (v. 100% last, 230 V):	ca 85 %
Current limiting:	Strømbegrensning:	Yes / Ja
Insulation class:	Isolasjonsklasse:	I
Insulation voltage	Isolasjonsspenning	
• Primary - secondary:	• Primær - sekundær:	4000 VAC / 5640 VDC
Safety:	Sikkerhet:	EN 60601-1, EN 60950, UL 60601-1
	(99XX only)	
EMC standards	EMC standarder	
• Medical:	• Medisinsk:	EN 60601-1-2
• Emission:	• Emisjon:	EN 61000-6-3
• Immunity:	• Immunitet:	EN 61000-6-1
Output terminal:	Utgangsterminaler:	Cable / Kable incl. / excl. plug
Dimensions (LxWxH):	Ytre mål (LxBxH):	107 x 67 x 36,5mm (9920-21-22, 2720)
Weight:	Vekt:	250g (450g IP67 vers.)

* Some technical specifications may differ for other models and voltage versions. / Visse tekniske data kan variere for de forskjellige modeller og spenningsversjoner.

Voltage versions - Spenningsversjoner

Output / Utgang (V)	Max. current / Maks. strøm (A)	Max. output power / Maks. utgangseffekt (W)
5 *	3,5	17,5
6 **	5	30
9 *	3	27
13,2	3	40
16	2,5	40
24	1,6	40
48	0,8	40

* UL-approval pending (99XX only)/
Avventer
UL-godkjenning
(kun 99XX)

** 2720/21 only

www.mascot.com

sales@mascot.no

TS070709

Main Office NORWAY
Box 177
N-1101 Fredrikstad
+47 69 36 43 00

Mascot UK
Box 2090, Salisbury
Wiltshire SP2 2BH
+44 172 250 4853

Mascot DE, BENELUX
Hirschbergstr. 28/7
D-74838 Limbach
+49 628 795 140

Mascot DE, CH, AT
Tettmanger Str. 52
D-88239 Wangen
+49 752 895 1677

Mascot FRANCE
38 rue Leo Lagrange
F-94270 Le Kremlin Bicêtre
+33 146 587 185

Mascot BALTIC, RUSSIA
Peterburi tee 81
11415, Tallin, Estonia
+372 555 21 121

Mascot SWEDEN
Box 177
N-1601 Fredrikstad
+46 526 14025