

Max. 61 m³/h

DC centrifugal fans

97 x 93.5 x 33 mm



- **Material:** Scroll housing: GRP¹⁾
Impeller: GRP¹⁾
- **Direction of air flow:** Axial: Intake,
Centrifugal: Exhaust
- **Connection:** via single wires AWG 26, TR 64
- **Highlights:** Forward-curved impeller
- **Weight:** 170 g
- **Possible special versions:**
(See chapter DC fans - specials):
 - Speed signal
 - Go / NoGo alarm
 - Alarm with speed limit
 - External temperature sensor
 - Internal temperature sensor
 - PWM control input
 - Analog control input
 - Moisture protection

1) Fiberglass-reinforced plastic



Series RL 65

Nominal data

	Air flow	Air flow	Nominal voltage	Voltage range	Sound power level	Sinter sleeve bearings Ball bearings	Power consumption	Nominal speed	Temperature range	Service life L ₁₀ (40 °C) ebm-papst standard	Service life L ₁₀ (T _{max}) ebm-papst standard	Life expectancy L ₁₀ IPC (40 °C) see page 17	Curve
Type	m ³ /h	cfm	VDC	VDC	Bel(A)	■ / ■	Watts	rpm ⁻¹	°C	Hours	Hours	Hours	
RL 65-21/12	56	32,9	12	6.8...13.8	6.6	■ / ■	15.0	4 500	-20...+70	60 000 / 30 000	102 500	102 500	①
RL 65-21/12 H	61	35,8	12	6.8...13.2	6.8	■ / ■	19.2	4 900	-20...+55	55 000 / 40 000	92 500	92 500	②
RL 65-21/14	56	32,9	24	12...26.4	6.6	■ / ■	14.0	4 500	-20...+70	60 000 / 30 000	102 500	102 500	①
RL 65-21/14 H	61	35,8	24	12...26.4	6.8	■ / ■	18.0	4 900	-20...+60	55 000 / 35 000	92 500	92 500	②

Subject to change

Snap-in fins for easy latch



Air performance measured according to: ISO 5801.
Installation category A, without contact protection.
Noise: Total sound power level L_{WA} ISO 103002 measured on a hemisphere with a radius of 2 m.
Sound pressure level L_{PA} measured at 1 m distance from fan axis.
The values given are applicable only under the specified measuring conditions and may differ depending on the installation conditions.
In the event of deviation from the standard configuration, the parameters must be checked after installation!
For detailed information see
<http://www.ebmpapst.com/general conditions>

