




ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.



SPC—F005.DWG

REVISIONS			DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398							
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE		
			VEE	10-08-10	Jaggar	14-08-10	XXX	24-08-10		

With Fuse



Mounting Hole



Dimensions : Inches (mm)

Agency Approvals: UL Recognized - Guide IZLT2, File E14853
CSA Certified - CLASS 6225-01, FILE E47235
Temperature Rating: 150°C.
Current: 30A
Voltage: 250 VAC
CE Logo denotes compliance with European Union Low Voltage Directive (50-1000 VAC, 75-1500 VDC)

General Information:
Bayonet Type Knob
For 1/2" x 1-1/4" Fuses.
Vibration Resistant.
For panels up to 5/16" (7.9mm) thick

Part Number Table

Description	Part Number
Panel Mount Fuseholder	MCHKP-RH

DISCLAIMER:

ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:	DRAWING TITLE:			
VEE	10-08-10	Panel Mount Fuseholder			
CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	
Jogon	14-08-10	A	XXX	92N5191	REV
APPROVED BY:	DATE:	SCALE:	NTS	U.O.M.: Millimeters	SHEET: 1 OF 1
XXX	24-03-10				