


ENERGIZER 317

SILVER OXIDE



Industry Standard Dimensions



DESIGNED FOR USE ON CONTINUOUS LOW DRAIN

Specifications

Chemical System: Silver Oxide (Zn/Ag₂O)

Nominal Voltage: 1.55 Volts

Typical Capacity: 12.5 mAh* (to 1.3 volts)

Capacity Test: 68K ohm continuous drain at 21°C


Typical Weight: 0.18 grams (0.006 oz.)

Typical Volume: 0.04 cubic centimeters (0.002 cubic inch)

Impedance (40 Hz): 55 to 65 ohms

* Varies according to the applied load, temperature, and cutoff voltage.


Cross Section



Typical Discharge Characteristics

Typical Performance at 21°C (70°F)

Schedule: Continuous
Typical Drain @1.55V:
0.023 milliamperes
Load: 68K ohm




Schedule	Typical Drains at 1.55V (milliamperes)	Load (ohm)	Cutoff (hours)
Continuous	0.023	68K	543


Temperature Characteristics

Typical Performance at Low Discharge Rates

Service Effects



Storage Effects



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication.
©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.