

Terminal Block

12Way, 20A




**RoHS
Compliant**



Specifications:

Current Rating	: 20A 300V AC
Insulation Withstands Volt	: 2,000V AC min
Insulation Resistance	: >2,000MΩ 500V DC
Wire Range	: 12 to 22AWG
Screw Torque	: 12lb-inch



Dimensions:

Pitch : 9.5mm (0.374")		
Poles	A	B
12	131.2	124

Dimensions : Millimetres

No	Part Name	Material	Plating/Finish	Remark
1	Insulating Body	PC	-	Black
2	Terminal	Brass	Tin plated	-
3	Screw	Steel #6-32	Ni Plated	-

Part Number Table

Description	Part Number
Terminal Block, 12Way, 20A	T64 12WAY

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.