


# 70-402-1 Socket/10 Amp Rating, 300 Volts



Printed Circuit  
Board Mounting



## BOLD-FACED PART NUMBERS ARE NORMALLY STOCKED

### Standard Part Number

### Description

**70-402-1**

8-Pin, Printed Circuit Terminals

## General Specifications (UL 508)

| Characteristics                     | Units | Value                     |
|-------------------------------------|-------|---------------------------|
| Number of Terminals                 |       | 8                         |
| <b>Electrical Rating</b>            |       |                           |
| Nominal Voltage Rating              | Volts | 300                       |
| Nominal Current Rating              | Amps  | 10                        |
| <b>Dielectric Strength</b>          |       |                           |
| Output to Input Terminals           | V rms | 1500                      |
| Output to Adjacent Output Terminals | V rms | 1500                      |
| <b>Temperature</b>                  |       |                           |
| Operating Range:                    | °C    | - 40 to + 80              |
| Storage Range:                      | °C    | - 40 to+ 105              |
| <b>Construction</b>                 |       |                           |
| Internal Metal Tracks               |       | Copper Alloy, Zinc Plated |
| Terminals                           |       | Copper Alloy, Zinc Plated |
| <b>Miscellaneous</b>                |       |                           |
| Socket Mounting:                    |       | Printed Circuit           |
| Connection Method                   |       | Solder                    |
| Flamability Rating                  | Class | 94V-0                     |
| Body Color                          |       | Light Gray                |
| Product Certification               |       | UL, CSA                   |
| Conformance                         |       | CE, RoHS                  |
| Weight                              | grams | 6.5                       |

