

Double Row Terminal Blocks

300 Series Kulka® 672 GP Series

600 Volts



CE

Top Mounted Hardware is .250" Wide

MM = Dim x 25.4

Hardware Options: (Hardware options may affect ratings - consult factory)

MSP	KULKA		
(F1)	KT55	= Full Quick Connect (0° Flat)	See Page 96
(F2)	KT56	= Full Quick Connect (45° Bend)	See Page 96
(F3)	KT57	= Full Quick Connect (90° Bend)	See Page 96
(S)	ST	= Full Solder	See Page 97
(LL 300)	J 602	= Line to Line Jumper	See Page 99
(HS)	3/4 ST	= Half Solder	See Page 97
(HF1)	KT61	= Half Quick Connect (0° Flat)	See Page 96
(HF2)	KT62	= Half Quick Connect (45° Bend)	See Page 96
(HF3)	KT63	= Half Quick Connect (90° Bend)	See Page 96
(SP)	3786	= Sems Pressure Saddle Screw	See Page 99
(SPSE)		= Sems Pressure Saddle Screw with External Tooth Lock Washer	
	LWW	= Feed Thru Wire Wrap (1.00)	
(L)	Y	= Feed Thru Solder (.437)	
	YSY	= Feed Thru Solder (.625)	
	PSB	= Phil-Slot Brass Screw	

