

Fuse holder terminal block with screwed plug for 5 x 20 mm or 5 x 25 mm fuses

Screw clamp

DIN 1 - DIN 3




End stop		th. 9 mm	BADL	V0	1SNA 399 903 R0200
End stop		th. 10 mm	BAM2	V2	1SNA 206 351 R1600
End stop		th. 10 mm	BAM2 V0	V0	1SNA 296 351 R0000
Rail		35 x 7,5 x 1	PR3.Z2		1SNA 174 300 R1700
Rail		35 x 15 x 2,3	PR4		1SNA 168 500 R1200
Rail		35 x 15 x 1,5	PR5		1SNA 168 700 R2200
Rail		32 x 15 x 1,5	PR1.Z2		1SNA 163 050 R0400

Other end stops, rails and accessories : see section on accessories.

Notes

The use of some accessories may decrease the block's voltage rating. For more information, consult us.

Accessories




1	End section	grey
2	Standard jumper bar	57 A
3	IDC jumper	
4	Fuse 5 x 20	250 V
	Fuse 5 x 25	250 V
	Fast acting according to DIN 41576.1	



R See section on markers marking method

MB 10/12.SF...

Spacing 12 mm (.473")



12 mm block, no fusion indicator - for 5 x 20 mm or 5 x 25 mm fuses

Colour	Type	Part numbers
Grey/5x20 mm	MB 10/12.SF	1SNA 111 033 R0300
Grey/5x25 mm	MB 10/12.SF1	1SNA 111 035 R0500

Characteristics

Wire size		NFC DIN	UL	CSA
Screw clamp	Rigid	0,5-16 mm ²	18-6 AWG	18-6 AWG
	Flexible	0,5-10 mm ²	18-6 AWG	18-6 AWG


Voltage		500 V Gr.C (1)	600 V (1)	250 V
Rated				
Impulse withstand				
Pollution degree				

Current		10 A	15 A	15 A
Rated				

Wire size		10 mm ²	6 AWG	6 AWG
Rated / Gauge				
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	
13 mm .512"	6 mm .236"	1,2-1,4 Nm 10.6-12.3 lb.in	IP 10	

MB 10/12.SF...

Spacing 12 mm (.473")



12 mm block with neon fusion indicator for fuses 5 x 20 mm.

Colour	Type	Part numbers
Grey/110-220V (2)	MB 10/12.SFL	1SNA 111 034 R0400
Grey/LED 24 V (3)	MB 10/12.SFD	1SNA 111 037 R0700

Characteristics

Wire size		NFC DIN	UL	CSA
Screw clamp	Rigid	0,5-16 mm ²	18-6 AWG	18-6 AWG
	Flexible	0,5-10 mm ²	18-6 AWG	18-6 AWG

Voltage		500 V Gr.C (1)	600 V (1)	250(SFL) 24(SFD)
Rated				
Impulse withstand				
Pollution degree				

Current		10 A	15 A	15 A
Rated				

Wire size		10 mm ²	6 AWG	6 AWG
Rated / Gauge				
Wire stripping length	Recomm. screwdriver	Recomm. torque	Protection	
13 mm .512"	6 mm .236"	1,2-1,4 Nm 10.6-12.3 lb.in	IP 10	

Type	Part numbers		
FEM12S V2	th. 3 mm	1SNA 117 628 R2200	
BJS12 (2)	20 poles	1SNA 177 653 R0700	
Screw for BJS		1SNA 163 574 R2200	
Washer for BJS		1SNA 163 633 R2500	
AD2,5		1SNA 114 205 R2000	
FU520	0,5 A	1SNA 008 288 R1500	
	1 A	1SNA 008 290 R1300	
	2 A	1SNA 008 291 R0000	
	3,15 A	1SNA 008 289 R1600	
	5 A	1SNA 008 292 R0100	
FU525	1,6 A	1SNA 167 546 R2200	
	2 A	1SNA 167 547 R2300	
	2,5 A	1SNA 167 548 R0400	
	4 A	1SNA 167 549 R0500	
	6,3 A	1SNA 167 550 R0200	

Type	Part numbers		
FEM12S V2	th. 3 mm	1SNA 117 628 R2200	
AD2,5	24 A	1SNA 114 205 R2000	
FU520	0,5 A	1SNA 008 288 R1500	
	1 A	1SNA 008 290 R1300	
	2 A	1SNA 008 291 R0000	
	3,15 A	1SNA 008 289 R1600	
	5 A	1SNA 008 292 R0100	

RC65 - RC610 Sides of block

Note : (1) Insulation voltage of terminal block - operating voltage : according to fuse.
(2) Use of these accessories requires the user to cut out the partition.

RC65 - RC610 Sides of block