



Fuse holder terminal blocks for fuses 5x20 mm .197x.787 in. and 5x25 mm .197x.984 in.


Screw clamp  DIN 1 - DIN3



M 4/8.SF



M 4/8.SFL



M 4/8.SN



BAM



FEM8S

M 4/8.SF- 4 mm² blocks - 8 mm .315" spacing

Characteristics

		IEC NFC DIN	UL	CSA
Wire size mm ² / AWG	Solid	0.5 - 6	22-12 AWG	22-12 AWG
	Stranded	0.5 - 4		
Voltage	V	630 (1)(2)	600 (1)	250
Current	A	6.3	10	10
Rated wire size	mm ² / AWG	4 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	9.5 mm / .37"		
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in		

(1) Insulation voltage of terminal block - operating voltage : according to fuse.

(2) 400 V for block M 4/6.SFT

Selection

Description	Type	Order P/N	Packaging	Weight kg
Standard block grey 	M 4/8.SF	1SNA 115 657 R2500	50	
Block with test socket Ø2 mm grey 	M 4/8.SF	1SNA 115 662 R2200	50	
Standard block orange 	M 4/8.SF2	1SNA 105 135 R1100	50	
Standard block beige V0 	M 4/8.SF.V0	1SNA 195 657 R2600	50	

M 4/8.SFL - 4 mm² blocks - 8 mm .315" spacing

Characteristics

		IEC NFC DIN	UL	CSA
Wire size mm ² / AWG	Solid	0.5 - 6	22-12 AWG	22-12 AWG
	Stranded	0.5 - 4		
Voltage	V	400	600	250
Current	A	6.3	10	10
Rated wire size	mm ² / AWG	4 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	9.5 mm / .374"		
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.7 lb.in		

Selection

Description	Type	Order P/N	Packaging	Weight kg
Block with fusion indicator neon grey 	M 4/8.SFL	1SNA 115 661 R2100	50	
Block with fusion indicator 24V grey 	M 4/8.SFD	1SNA 115 663 R2300	50	

M 4/8.SN - 4 mm² blocks - 8 mm .315" spacing

Characteristics

		IEC NFC DIN	UL	CSA
Wire size mm ² / AWG	Solid	0.5 - 6	22-12 AWG	24-12 AWG
	Stranded	0.5 - 4		
Voltage	V	630 (1)	600	250
Current	A	6.3	10	10
Rated wire size	mm ² / AWG	4 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	9.5 mm / .37"		
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in		

(1) Insulation voltage of terminal block - operating voltage : according to fuse.

Selection

Description	Type	Order P/N	Packaging	Weight kg
Standard block grey body/blue grip 	M 4/8.SN	1SNA 115 659 R0700	50	
Standard block beige body/blue V0 grip 	M 4/8.SN.V0	1SNA 195 659 R0000	50	

Accessories

End stop	BAM	9.1 mm	1SNA 103 002 R2600	50
End section	grey 	FEM8S 1.5 mm	1SNA 116 951 R1500	20
	orange 	FEM8S 1.5 mm	1SNA 103 923 R1500	20