

RB Series RB2XDV/15, RB2X110/10 and RB3X230/10



CE - Certified to EMC Directive 89/336/EEC.
Complies with low voltage directive 2006/95/EC.
High voltage transient and polarity reversal protection fitted.
Operating temperature: -20°C to +50°C.



IP65	0.27kg

RB2XDV/15 15W	60cd (amber)	125/min	single flash	10 – 30Vdc	1.5A@12Vdc 0.75A@24Vdc
RB2X110/10 10W	50cd (amber)	110/min	single flash	90 – 125Vac	130mA @110Vac
RB3X230/10 10W	50cd (amber)	94/min	single flash	207 – 253Vac	70mA @230Vac

Features:

A very bright low voltage and mains voltage beacon with a fast flash rate.

- No moving parts – maintenance free
- Low power consumption
- Compact design
- 3,000 hours tube life
- 12 months’ guarantee

Materials:

Polycarbonate lens, ABS base.

Lens Colour	RB2XDV/15 (10 – 30Vdc) 15W	RB2X110/10 (110Vac) 10W	RB3X230/10 (230Vac) 10W
Amber	470002	408022	408052
Blue	470004	408024	408054
Red	470003	408023	408053
Clear	470001	408021	408051
Green	470005	408025	408055

Drilling for Panel Mounting (ISO 4148)