

flare MOVE 24VDC-1W-6A




flare MOVE 24VDC-1W-6A

Pluggable coupling relay


24 V DC

80.010.4502.0

- Pluggable coupling relay
- Input voltage range 18 ... 28,8 V DC
- 1 changeover contact
- Mounting width 6,2 mm



Wiring diagram



Dimensional diagram

Technical Data

flare MOVE 24VDC-1W-6A	Order no. 80.010.4502.0
Coil circuit	
Operating voltage	24 V DC
Minimum input voltage	18 V DC
Maximum input voltage	28,8 V DC
Nominal input current	9 mA
Nominal input capacity	0,2 W
Status display	LED green
Switching characteristics	
Contacts	1 changeover contact
Contact material	AgSnO ₂
Nominal switching voltage	250 V AC
Maximum switching voltage	400 V AC
Maximum continuous current	6 A AC/DC (see Fig. 1 Load limiting curves)
Maximum starting current	10 A
Maximum switching current	(see Fig. 1 Load limiting curves)
DC1 30 / 110 / 220 V DC	6 A / 0,2 A / 0,15 A
Maximum breaking capacity (ohmic load)	1500 V A / 150 W
Maximum switching capacity AC 15	300 V A
Minimum selectable voltage	12 V AC/DC
Minimum selectable current	10 mA AC/DC




Fig. 1 Load limiting curves

**flare MOVE 24VDC-1W-6A****Technical Data**

flare MOVE 24VDC-1W-6A	Order no. 80.010.4502.0
Minimum switching capacity	500 mW
Mechanical life	10×10^6
Electrical life	60×10^3 (see Fig. 1 Load limiting curves)
Maximum switching frequency	0,1 Hz
Pick-up delay	7 ms
Release delay	11 ms

General Data

Width	6,2 mm
Height	87,3 mm
Depth	76,6 mm
Rated voltage	250 V
Isolation voltage of input/output	4 kV eff.
Ambient temperature	-40 ... +55° C
Storage temperature	-40 ... +55° C
Degree of protection (IP)	IP20
Mounting rail	TS35 acc. EN 60715

Connection Data

Connection type	Screw terminals
Wire range fine-stranded min	0,25 mm ²
Wire range fine-stranded max	2,5 mm ²
Wire range solid min	0,25 mm ²
Wire range solid max	2,5 mm ²
Torque	0,5 Nm
Connectable via pluggable jumper	20

Approvals

Conformity	CE-conformity
Approvals and Standards	cURus