

General Information

Extended Product Type:	DR4/6.1
Product ID:	1SNA110491R1700
EAN:	3472591104912
Catalog Description:	DR4/6.1
Long Description:	DR4/6.1 Screw Clamp Terminal Blocks Miniblocks

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Screw Clamp Terminal Blocks

Ordering

EAN:	3472591104912
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Weight:	6.00 g
---------------------	--------

Container Information

Package Level 1 Units:	50 piece
Package Level 1 Width:	66 mm
Package Level 1 Height:	41 mm
Package Level 1 Length:	150 mm
Package Level 1 Gross Weight:	0.3 kg
Package Level 1 EAN:	3472591104912
Package Level 2 Units:	1750 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	150 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	10.85 kg
Package Level 3 Units:	84000 piece
Product Packing Type:	Box

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Technical UL/CSA

Flammability According to UL94:	V0
---------------------------------	----

Additional Information

Color:	Grey
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22-4 mm ² Screw Clamp / Rigid 1x 0.2-4 mm ²
Connection Type:	Screw clamp
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	2500 V
Function:	Miniblocks
Gauge(s) of Form:	A4
IIT Publishing Status:	Level 0 - Information enabled
Mounting on DIN Rail:	TH15-5.5 (15 x 5.5 mm Mounting Rail) acc. to IEC 60715
Product Main Type:	DR4/6.1
Product Name:	Terminal block
Rated Cross-Section:	4 mm ²
Rated Current (I _n):	Main Circuit 30 A
Rated Impulse Withstand Voltage (U _{imp}):	4 kV
Rated Short-time Withstand Current (I _{cw}):	for 1.0s 480 A
Rated Voltage (U _r):	500 V
Recommended Screw Driver:	4
Spacing:	6 mm
Sub-Function:	Feed-through
Sub-Function 2:	For DIN 2 Rail with partition
Tightening Torques:	acc. IEC 60947-1 0.5 N·m

	Manufacturer 0.8 N·m
Wire Stripping Length:	9.5 mm

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225001C1000
GOST Certificate:	1SND161005A1103

Classifications

Object Classification Code:	X
-----------------------------	---

