



Connectors

HelaCon Plus

HelaCon connectors are used for fast, easy and reliable connection and distribution of cable and conductors in electrical installation applications.

Features and Benefits

- Sophisticated push-in wire connector
- For professional cable connections in electrical installations
- Double spring for easy assembly
- Supports installers in difficult situations like overhead work
- Correct installation can be visually checked through transparent housing
- Different colour codes for easy identification of size
- Separate voltage test entry on front
- Safe application, installation and maintenance



One Step to the Web!



Connectors of the HelaCon Plus family offering multiple sizes and colours.



A huge variety of connectors from 2 to 8 poles is available according to the application. The transparent housings allow a quick and easy checking of the conductor fitting.


MATERIAL	Polycarbonate (PC)
Max Current	24 A
Max Voltage	450 V
Wire Range (VDE)	0.5 to 2.5 mm ² solid / stranded (max. 7 cores)
Stripping Length	11 mm
Flammability	UL94 V2
Operating Temperature	-30 °C to +105 °C
Specifications	CE, cULus, DEMKO, ENEC, FIMKO, GL, KEMA-KEUR, NEMKO, SEMKO, VDE

HF ✓

RoHS ✓





For product specific approvals and specifications please refer to the Appendix.



Connectors

HelaCon Plus

HelaCon Plus wire connector
front view

HelaCon Plus wire connector side view

TYPE	Drawing	Number of Conductors	Colour	Width (W)	Height (H)	Depth (D)	Pack Cont.	Article-No.
HECP-2		2	Transparent (CL), Yellow (YE)	11.8	10.5	19.0	100 pcs.	148-90000
HECP-3		3	Transparent (CL), Orange (OG)	15.9	10.5	19.0	100 pcs.	148-90001
HECP-4		4	Transparent (CL)	20.1	10.5	19.0	75 pcs.	148-90002
HECP-5		5	Transparent (CL), Blue (BU)	24.2	10.5	19.0	50 pcs.	148-90003
HECP-6		6	Transparent (CL), Violet (VT)	28.4	10.5	19.0	50 pcs.	148-90004
HECP-8		8	Transparent (CL), Grey (GY)	36.7	10.5	19.0	40 pcs.	148-90005

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.

For product specific approvals and specifications
please refer to the Appendix.