




Part Number	Fan series	Dimensions LZ 32..					
LZ32-2	8000	Finger Guards	Mounting	B	C	D	E
LZ32-3	8000	LZ 32-2	A 1	3.15 (80)	2.82 (71.5)	.28 (7)	1.34 (34)
LZ32P	8000	LZ 32-3	A 3	3.15 (80)	2.82 (71.5)	.28 (7)	1.34 (34)
LZ23-2	3000	LZ23-2	A 1	3.64 (92.5)	3.25 (82.5)	.26 (6.5)	1.81 (46)
LZ23-3	3000	LZ23-3	A 3	3.64 (92.5)	3.25 (82.5)	.26 (6.5)	1.81 (46)
LZ30-5	9000	LZ30-5	A 2	4.69 (119)	4.14 (105)	.26 (6.5)	1.97 (50)
LZ30-6	9000	LZ30-6	A 4	4.69 (119)	4.14 (105)	.26 (6.5)	1.97 (50)
LZ30P	9000	LZ33-1	A 2	5.0 (127)	4.47 (113.5)	.26 (6.5)	1.97 (50)
LZ30-5	4000	LZ33-2	A 4	5.0 (127)	4.47 (113.5)	.26 (6.5)	1.97 (50)
LZ30-6	4000						
LZ30P	4000						
LZ33-1	5200						
LZ33-2	5200						
LZ33-1	5900						
LZ33-2	5900						

Technical drawing of a fan assembly. The left view shows a side profile with dimension D indicating the width of the finger guard. The right view shows a top-down perspective of the fan blades and mounting structure, with dimension A indicating the mounting distance.


Technical drawing of a screw connection. It shows two types of connections, A1 and A2. A1 is a standard screw connection with a diameter of 0.18 (4.5) and a length of 15. A2 is a more complex connection with a diameter of 0.18 (4.5) and a length of 0.32 (8). The drawing also shows a 90-degree angle for the screw connection.




Screw connection



Barbed inserts



LZ30P



LZ32P

