

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744324063

LF




Bezeichnung : SPEICHERDROSSEL WE-HC

description : POWER-CHOKE WE-HC

DATUM / DATE : 2006-06-02

A Mechanische Abmessungen / dimensions :




A	10,5 ± 0,5	mm
B	10,0 ± 0,4	mm
C	3,9 ± 0,2	mm
D	2,35 ref.	mm
E	5,6 ref.	mm
F		mm
G		mm
H		mm

B Elektrische Eigenschaften / electrical properties :

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	100 kHz / 0,1V	L_0	0,75	μH	± 20%
Nenn-Induktivität / rated inductance	100 kHz / 0,1V / 18A	L_N	0,62	μH	± 20%
DC-Widerstand / DC-resistance	@ 20° C	$R_{DC \text{ typ}}$	2,89	m Ω	typ.
DC-Widerstand / DC-resistance	@ 20° C	$R_{DC \text{ max}}$	3,45	m Ω	max.
Nennstrom / rated current	$\Delta T = 50 \text{ K}$	I_{DC}	18,0	A	typ.
Sättigungsstrom / saturation current	$\Delta L/L_0 = -30\%$	I_{sat}	27,0	A	typ.
Eigenres.-Frequenz / self.res.-frequency		SRF	110,0	MHz	ref.

C Lötpad / soldering spec. :



D Prüfgeräte / test equipment :

HP 4274 A für/for L und/and Q
HP 34401 A für/for I_{DC} und/and R_{DC}

E Testbedingungen / test conditions :

Luftfeuchtigkeit / humidity: 33%
Umgebungstemperatur / temperature: + 25°C

F Werkstoffe & Zulassungen / material & approvals :

Kernmaterial / core material: WE-Superflux 200
Draht / wire: Flatwire/ Flachdraht UL94-V0; 2UEWF 155°C

G Eigenschaften / granted properties :

Arbeitstemperatur / operating temperature: -40°C - +150°C
Umgebungstemp. / ambient temperature: -40°C - +100°C
It is recommended that the temperature of the part does not exceed 150°C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer			
		RST	Version 5	2006-06-02
Datum / date	Unterschrift / signature	ME	Version 4	2005-04-18
	Würth Elektronik	MST	Version 3	2004-10-11
		SST	Version 2	2004-02-02
		JH	Version 1	2000-12-06
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.com

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744324063

LF




Bezeichnung : **SPEICHERDROSSEL WE-HC**

description : **POWER-CHOKE WE-HC**

DATUM / DATE : 2006-06-02

H Induktivitätskurve / Inductance curve :

Induktivität vs Strom (typ.)
Inductance vs Current (typ.)



Freigabe erteilt / general release:	Kunde / customer			
.....		RST	Version 5	2006-06-02
Datum / date	Unterschrift / signature	ME	Version 4	2005-04-18
	Würth Elektronik	MST	Version 3	2004-10-11
		SST	Version 2	2004-02-02
.....		JH	Version 1	2000-12-06
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744324063

LF




WÜRTH ELEKTRONIK

Bezeichnung :

description :

DATUM / DATE : 2006-06-02

I Temperaturanstieg / Temperature rise curve :



Freigabe erteilt / general release:	Kunde / customer			
		RST	Version 5	2006-06-02
Datum / date	Unterschrift / signature	ME	Version 4	2005-04-18
	Würth Elektronik	MST	Version 3	2004-10-11
		SST	Version 2	2004-02-02
		JH	Version 1	2000-12-06
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

<http://www.we-online.com>

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744324063

LF





Bezeichnung : **SPEICHERDROSSEL WE-HC**

description : **POWER-CHOKE WE-HC**


DATUM / DATE : 2006-06-02

J Rollenspezifikation / tape and reel specification :




Gurtspezifikation / Tape specification:

A	10,85 ± 0,1	mm
B	16,0 ± 0,1	mm
C	1,50^{+0,1}_{-0,0}	mm
D	1,50^{+0,1}_{-0,0}	mm
E	4,00 ± 0,1	mm
F	2,00 ± 0,1	mm
G	1,75 ± 0,1	mm
H	11,5 ± 0,1	mm
I	11,65 ± 0,1	mm
J	4,30 ± 0,1	mm
T	0,35 ± 0,05	mm
W	24,0 ± 0,3	mm



Rollenspezifikation / Reel specification:

a	330,0 ± 0,5	mm
b	20,20 ± 0,1	mm
c	13,00^{+0,5}_{-1,0}	mm
d	100,0 ± 1,0	mm



The Force for tearing off cover tape is
20 to 70 grams in arrow direction

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

RST	Version 5	06-06-02
ME	Version 4	05-04-18
MST	Version 3	04-10-11
SST	Version 2	04-02-02
JH	Version 1	00-12-06
Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>