

Terminal Block - Eurostyle

RoHS
Compliant



Specification:

Material:


Insulator	: PA66
Insulator Colour	: Green
Contact	: Copper, Tin plated.

Electrical:

Operation Voltage	: 300V AC Max.
Current Rating	: 8A Max. per Pole
Contact Resistance	: 20mΩ Max.
Insulation resistance	: 500MΩ Min. @ DC500V
Dielectric withstanding voltage	: 1,600V AC for 1 minute

Environmental:

Operating Temperature	: -40°C to +105°C
Recommended Soldering Temp.	: 235°C for 5 sec.



Dimensions : Millimeters

Terminal Block - Eurostyle

Part Number Table

Description	Position	Part Number
Terminal Block, Eurostyle	2	EB3-02-B-180
	3	EB3-03-B-180
	4	EB3-04-B-180
	5	EB3-05-B-180
	6	EB3-06-B-180
	8	EB3-08-B-180
	9	EB3-09-B-180
	10	EB3-10-B-180
	11	EB3-11-B-180
	12	EB3-12-B-180
	13	EB3-13-B-180
	14	EB3-14-B-180
	15	EB3-15-B-180
	16	EB3-16-B-180

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com

