

General Information

Extended Product Type:	BAM4
Product ID:	1SNK900001R0000
EAN:	3472599097254
Catalog Description:	BAM4 End Stop - Dark Grey
Long Description:	- Give efficient support to the SNK terminal blocks assemblies thanks to the BAM4 double gripping rail contact, - Ease the assemblies identification with the BAM4 marking location compatible with all SNK markers and labels.

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks Accessories » End Stops

Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Color:	Dark Grey

Dimensions

Product Net Height:	53.5 mm
Product Net Length:	35 mm
Product Net Depth:	35 mm
Product Net Weight:	14 g
Product Net Width:	10 mm

Technical

Spacing:	10 mm
Connection Type:	Screw clamp
Function:	End Stops
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Recommended Screw Driver:	5.5 mm
Suitable For:	RGW2.5 RGW2.5-PE RGW2.5-T RGW25-M5 RGW25-M6 RGW6 RGW6-PE RGW6-R1 RGW6-ST-1 RGW6-T ZDK2.5-22 ZDK4-22 ZDP2.5-11 ZDP2.5-22 ZDP2.5-D1 ZDP2.5-D2 ZDS4-22 ZDS4-22-R1 ZK10 ZK10-3P ZK10-PE ZK10-PE-3P ZK16 ZK16-3P ZK16-PE ZK16-PE-3P ZK2.5 ZK2.5-3P ZK2.5-4P ZK2.5-CH-4P ZK2.5-PE ZK2.5-PE-3P ZK2.5-PE-4P ZK2.5-S ZK2.5-S-4P

ZK2.5-SF
ZK2.5-SF-R
ZK2.5-SP
ZK2.5-SP-4P
ZK2.5-S-R1
ZK4
ZK4-3P
ZK4-4P
ZK4-PE
ZK4-PE-3P
ZK4-PE-4P
ZK6
ZK6-3P
ZK6-PE
ZK6-PE-3P
ZP2.5
ZP2.5-3P
ZP2.5-4P
ZP2.5-D1
ZP2.5-D2
ZP2.5-PE
ZP2.5-PE-3P
ZP2.5-PE-4P
ZP2.5-S
ZP2.5-SP
ZS10
ZS10-PE
ZS10-PE-R1
ZS10-R1
ZS10-S
ZS10-SF
ZS10-SF-R
ZS10-SP
ZS10-S-R2
ZS10-ST
ZS10-ST-1
ZS10-ST-T4
ZS16
ZS16-PE
ZS25
ZS25-PE
ZS4
ZS4-PE
ZS4-PE-R2
ZS4-R1
ZS4-R2
ZS4-S
ZS4-SF
ZS4-SF1
ZS4-SF1-R
ZS4-SF1-T
ZS4-SF-R
ZS4-SF-T
ZS4-SP
ZS4-SP-R1
ZS4-SP-T2
ZS4-SP-T2-R1
ZS4-S-R1
ZS4-S-R2
ZS4-S-R3
ZS4-S-T
ZS4-S-T-R1
ZS6
ZS6-3S
ZS6-3S-PE
ZS6-4S
ZS6-4S-PE
ZS6-PE
ZS6-S
ZS6-S-4S-T

Technical UL/CSA

Flammability According to UL94: V0

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6: Compliant

RoHS Status: Following EU Directive 2011/65/EC

Ambient Air Temperature: Operation -55 ... +110 °C

Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

Instructions and Manuals:	1SNK160027C0201
Data Sheet, Technical Information:	1SNK160016D0201
RoHS Information:	1SND230479F0206

Classifications

E-nummer:	2925146
ETIM 4:	EC001041 - End bracket for terminal block
ETIM 5:	EC001041 - End bracket for terminal block
ETIM 6:	EC001041 - End bracket for terminal block
Object Classification Code:	X

Container Information

Package Level 1 Width:	178 mm
Package Level 1 Length:	280 mm
Package Level 1 Gross Weight:	0.7 kg
Package Level 1 EAN:	3472599097254
Package Level 2 Units:	1000 piece
Package Level 3 Units:	24000 piece
Product Packing Type:	Bag
Package Level 1 Units:	50 piece

