



Holder / No. 562

PC Mount, for TR5®/TE5® Fuses



Holes in PCB



Specifications

Packaging

100 bulk (1000 pcs.)

Mounting

PC Board, 5.08mm pin spacing

Materials

Holder: Black Thermoplastic, UL94 V-0
Nylon 46
Terminals: Copper alloy; solderable
tinned

Electrical Data (23°C)

Rated Voltage: 250V
Max. Current/Power: 6.3A/1.6W

Minimum Cross Section

Conducting path - 0.1mm²

Unit Weight

0.12g



Order Information

Qty.	Order- Number	Series		Packaging
		562	0000	100



Specifications are subject to change without notice

Holder / No. 564

Surface Mount, for TR5®/TE5® Fuses



recommended Pad Layout (mm)



Packaging

100 Tape/Reel (1500 pcs.)
Carrier tape width 16 mm
Reel diameter 33 cm

Order Number

Holder No. 564 0000 100

Mounting

PC Board, 5.08mm pad spacing

Materials

Holder: Black Thermoplastic, UL94 V-0
Nylon 46
Terminals: Copper alloy; solderable
tinned

Electrical Data (23°C)

Rated Voltage: 250V
Max. Current/Power: 6.3A/1.6W

Minimum Cross Section

Conducting path - 0.1mm²

Unit Weight

0.44g



Order Information

Qty.	Order- Number	Series		Packaging
		564	0000	100

Specifications are subject to change without notice

Note: 1.00 means the number one with two decimal places. 1,000 means the number one thousand.