









SAFETY ISOLATING TRANSFORMER

POWER : 22VA
INPUT VOLTAGE : 230V
FREQUENCY : 50/60Hz
NOMINAL OUTPUT VOLTAGE : 2x18V

NON SHORT CIRCUIT PROOF TRANSFORMER
IP00
UL94V0
OPERATING TEMPERATURE : -25°C to 50°C
STORAGE TEMPERATURE : -25°C to 85°C
INSULATION CLASS (IEC85) : B
REQUIRED PROTECTION : 125mA FUSE ON PRIMARY

STANDARDS :
UL506 (File E111078)
CSA 22-2 (File E111078)
VDE (File Ref:1398300)
EN60950 (File Ref:1398300)
EN61558-1 (File Ref:1398300)
EN61558-2-6 (File Ref:1398300)
CE



Rev	Date	Modification	Dessiné	Visa
D				
C				
B				
A				

<u>Finition:</u>		<u>Tolérance générale:</u>	
<u>Finition:</u>		<u>General tolerance:</u>	
<u>Ech:</u> 1:1	<u>Matière:</u>		
	<u>Material:</u>		
<u>Dessiné par:</u>	ROUSSEL.Ch	<u>Date:</u>	06/09/2002
		<u>Visa:</u>	J.P.M.
DATA SHEET 44442			
EI 60x21			
		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLEGIEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44442	