









SAFETY ISOLATING TRANSFORMER

POWER : 30VA
INPUT VOLTAGE : 230V
FREQUENCY : 50/60Hz
NOMINAL OUTPUT VOLTAGE : 2x12V

NON SHORT CIRCUIT PROOF TRANSFORMER
IP00
UL94V0
OPERATING TEMPERATURE : -25°C to 50°C
STORAGE TEMPERATURE : -25°C to 85°C
INSULATION CLASS (IEC85) : B
REQUIRED PROTECTION : 160mA FUSE ON PRIMARY

STANDARDS :
UL506 (File E111078)
CSA 22-2 (File E111078)
VDE (File Ref:1398300)
EN60950 (File Ref:1398300)
EN61558-1 (File Ref:1398300)
EN61558-2-6 (File Ref:1398300)
CE



Rev	Date	Modification	Dessiné	Visa
D				
C				
B				
A				

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matériau:		
Material:			
Dessiné par: ROUSSEL.Ch	Date: 09/09/2002	Visa: J.P.M.	
DATA SHEET 44381 EI 66x23			
myrra		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLEGIEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS44381	