

## Base strip - MCV 1,5/ 4-GF-3,81 - 1830619

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.81 mm, Color: green, Contact surface: Tin, Mounting: Wave soldering



The figure shows a 10-position version of the product

### Why buy this product

- Versions with engagement noses for locking plugs with self-locking flanges
- Low-profile pin strips with compact pitches



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 250 pc                                                                                                  |
| GTIN                                 | <br>4 017918 051266 |
| Weight per Piece (excluding packing) | 2.13 g                                                                                                  |
| Custom tariff number                 | 85366990                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|                          |              |
|--------------------------|--------------|
| Length                   | 7.25 mm      |
| Pitch                    | 3.81 mm      |
| Dimension a              | 11.43 mm     |
| Constructional height    | 10 mm        |
| Length of the solder pin | 3.4 mm       |
| Pin dimensions           | 0,8 x 0,8 mm |
| Hole diameter            | 1.2 mm       |

#### General

|                           |                |
|---------------------------|----------------|
| Range of articles         | MCV 1,5/...-GF |
| Insulating material group | IIIa           |

## Base strip - MCV 1,5/ 4-GF-3,81 - 1830619

### Technical data

#### General

|                                        |        |
|----------------------------------------|--------|
| Rated surge voltage (III/3)            | 2.5 kV |
| Rated surge voltage (III/2)            | 2.5 kV |
| Rated surge voltage (II/2)             | 2.5 kV |
| Rated voltage (III/3)                  | 160 V  |
| Rated voltage (III/2)                  | 160 V  |
| Rated voltage (II/2)                   | 250 V  |
| Connection in acc. with standard       | EN-VDE |
| Nominal current $I_N$                  | 8 A    |
| Maximum load current                   | 8 A    |
| Insulating material                    | PBT    |
| Flammability rating according to UL 94 | V0     |
| Color                                  | green  |
| Number of positions                    | 4      |

#### Standards and Regulations

|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CSA    |
| Flammability rating according to UL 94 | V0     |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Base strip - MCV 1,5/ 4-GF-3,81 - 1830619

### Approvals

#### Approvals

#### Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / IECEx CB Scheme / CCA / EAC / cULus Recognized

#### Ex Approvals

#### Approvals submitted

#### Approval details

|                                                                                        |       |       |
|----------------------------------------------------------------------------------------|-------|-------|
| CSA  |       |       |
|                                                                                        | B     | D     |
| Nominal current I <sub>N</sub>                                                         | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub>                                                         | 300 V | 300 V |

|                                                                                                                             |       |
|-----------------------------------------------------------------------------------------------------------------------------|-------|
| VDE Gutachten mit Fertigungsüberwachung  |       |
|                                                                                                                             |       |
| Nominal current I <sub>N</sub>                                                                                              | 8 A   |
| Nominal voltage U <sub>N</sub>                                                                                              | 160 V |

|                                                                                                     |       |
|-----------------------------------------------------------------------------------------------------|-------|
| IECEx CB Scheme  |       |
|                                                                                                     |       |
| Nominal current I <sub>N</sub>                                                                      | 8 A   |
| Nominal voltage U <sub>N</sub>                                                                      | 160 V |

|                                |       |
|--------------------------------|-------|
| CCA                            |       |
|                                |       |
| Nominal current I <sub>N</sub> | 8 A   |
| Nominal voltage U <sub>N</sub> | 160 V |



|     |
|-----|
| EAC |
|-----|

## Base strip - MCV 1,5/ 4-GF-3,81 - 1830619

### Approvals

|                                |       |       |
|--------------------------------|-------|-------|
| cULus Recognized               |       |       |
|                                | B     | D     |
| Nominal current I <sub>N</sub> | 8 A   | 8 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

### Drawings



Type: MC 1,5/...-STF-3,81 with MCV 1,5/...-GF-3,81

### Dimensional drawing

