

## Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Plug component, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin



The figure shows a 10-position version of the product

### Why buy this product

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Allows connection of two conductors
- ✓ Screwable flange for superior mechanical stability



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 250 STK                                                                                                 |
| GTIN                                 | <br>4 017918 099930 |
| GTIN                                 | 4017918099930                                                                                           |
| Weight per Piece (excluding packing) | 3.600 g                                                                                                 |
| Custom tariff number                 | 85366990                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|             |         |
|-------------|---------|
| Length      | 16.1 mm |
| Height      | 11.1 mm |
| Width       | 24.3 mm |
| Pitch       | 3.5 mm  |
| Dimension a | 10.5 mm |

#### General

|                   |                  |
|-------------------|------------------|
| Range of articles | MC 1,5/...-STF   |
| Type of contact   | Female connector |

# Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

## Technical data

### General

|                                        |                                                                                                             |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Number of positions                    | 4                                                                                                           |
| Connection method                      | Screw connection with tension sleeve                                                                        |
| Insulating material group              | I                                                                                                           |
| Rated surge voltage (III/3)            | 2.5 kV                                                                                                      |
| Rated surge voltage (III/2)            | 2.5 kV                                                                                                      |
| Rated surge voltage (II/2)             | 2.5 kV                                                                                                      |
| Rated voltage (III/3)                  | 160 V                                                                                                       |
| Rated voltage (III/2)                  | 160 V                                                                                                       |
| Rated voltage (II/2)                   | 320 V                                                                                                       |
| Connection in acc. with standard       | EN-VDE                                                                                                      |
| Nominal current $I_N$                  | 8 A                                                                                                         |
| Nominal cross section                  | 1.5 mm <sup>2</sup>                                                                                         |
| Maximum load current                   | 8 A (with 1.5 mm <sup>2</sup> conductor cross section)                                                      |
| Insulating material                    | PA                                                                                                          |
| Flammability rating according to UL 94 | V0                                                                                                          |
| Internal cylindrical gage              | A1                                                                                                          |
| Stripping length                       | 7 mm                                                                                                        |
| Screw thread                           | M2                                                                                                          |
| Tightening torque, min                 | 0.22 Nm                                                                                                     |
| Tightening torque max                  | 0.25 Nm                                                                                                     |
| Note                                   | CR-MSTB may only be used after reflow soldering. CR-MSTB NAT HT may also be used prior to reflow soldering. |

### Connection data

|                                                                                       |                      |
|---------------------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                                    | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                                    | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                                 | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                                 | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve min.            | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.            | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.               | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.               | 0.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.                                                      | 28                   |
| Conductor cross section AWG max.                                                      | 16                   |
| 2 conductors with same cross section, solid min.                                      | 0.08 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                      | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                                   | 0.08 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                   | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 0.34 mm <sup>2</sup> |

# Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

## Technical data

### Connection data

|                                                                                         |                     |
|-----------------------------------------------------------------------------------------|---------------------|
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm <sup>2</sup> |
| Minimum AWG according to UL/CUL                                                         | 30                  |
| Maximum AWG according to UL/CUL                                                         | 14                  |

### Standards and Regulations


|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CSA    |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance


|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

Diagram




Dimensional drawing




Type: MC 1,5/...-STF-3,5 with MCV 1,5/...-GF-3,5

Diagram



Type: MC 1,5/...-STF-3,5 with MC 1,5/...-GF-3,5


Diagram



Type: MC 1,5/...-ST(F)-3,5 with MCV 1,5/...-G(F)-3,5 P... THR

## Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

Diagram



Type: MC 1,5/...-ST(F)-3,5 with MC 1,5/...-G(F)-3,5 P.. THR

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440309 |
| eCl@ss 9.0 | 27440309 |

ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002638 |
| ETIM 5.0 | EC002638 |
| ETIM 6.0 | EC002638 |

UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

### Approvals

Approvals

Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / IECCE CB Scheme / CCA / cULus Recognized / EAC

Ex Approvals

# Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

## Approvals

### Approval details

|                                |                                                                                   |                                                                                                                                                                                           |       |
|--------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                            |  | <a href="http://www.csagroup.org/services/testing-and-certification/certified-product-listing/">http://www.csagroup.org/services/testing-and-certification/certified-product-listing/</a> | 13631 |
|                                | B                                                                                 | D                                                                                                                                                                                         |       |
| mm²/AWG/kcmil                  | 28-16                                                                             | 28-16                                                                                                                                                                                     |       |
| Nominal current I <sub>N</sub> | 8 A                                                                               | 8 A                                                                                                                                                                                       |       |
| Nominal voltage U <sub>N</sub> | 300 V                                                                             | 300 V                                                                                                                                                                                     |       |

|                                            |                                                                                   |                                                                                                                                                                                                         |          |
|--------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx">http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx</a> | 40011723 |
|                                            |                                                                                   |                                                                                                                                                                                                         |          |
| mm²/AWG/kcmil                              | 0.2-1.5                                                                           |                                                                                                                                                                                                         |          |
| Nominal current I <sub>N</sub>             | 8 A                                                                               |                                                                                                                                                                                                         |          |
| Nominal voltage U <sub>N</sub>             | 160 V                                                                             |                                                                                                                                                                                                         |          |

|                                |                                                                                     |                                                           |                |
|--------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme                |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-56063-B1B2 |
|                                |                                                                                     |                                                           |                |
| mm²/AWG/kcmil                  | 0.2-1.5                                                                             |                                                           |                |
| Nominal current I <sub>N</sub> | 8 A                                                                                 |                                                           |                |
| Nominal voltage U <sub>N</sub> | 160 V                                                                               |                                                           |                |

|                                |                |  |  |
|--------------------------------|----------------|--|--|
| CCA                            | CCA/ DE1 34219 |  |  |
|                                |                |  |  |
| mm²/AWG/kcmil                  | 0.2-1.5        |  |  |
| Nominal current I <sub>N</sub> | 8 A            |  |  |
| Nominal voltage U <sub>N</sub> | 160 V          |  |  |

|                                |                                                                                     |                                                                                                                                                       |                 |
|--------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized               |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20110128 |
|                                | B                                                                                   | D                                                                                                                                                     |                 |
| mm²/AWG/kcmil                  | 30-14                                                                               | 30-14                                                                                                                                                 |                 |
| Nominal current I <sub>N</sub> | 8 A                                                                                 | 8 A                                                                                                                                                   |                 |
| Nominal voltage U <sub>N</sub> | 300 V                                                                               | 300 V                                                                                                                                                 |                 |

## Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

### Approvals

EAC



B.01742

### Accessories

#### Accessories

##### Labeled terminal marker

Marker card - SK 3,5/2,8:FORTL.ZAHLEN - 0804073



Marker card, Card, white, labeled, Horizontal: Consecutive numbers 1 - 10, 11 - 20, etc. up to 91 - 99, Mounting type: Adhesive, for terminal block width: 3.5 mm, Lettering field: 3.5 x 2.8 mm

### Screwdriver tools

Screwdriver - SZS 0,4X2,5 VDE - 1205037



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

### Additional products

Printed-circuit board connector - MCV 1,5/ 4-GF-3,5 P20 THRR56 - 1780707



Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black, Contact surface: Tin, Mounting: THR soldering, User information and design recommendations for through hole reflow technology can be found under "Downloads"

Printed-circuit board connector - MC 1,5/ 4-GF-3,5 P26 THR - 1789203



Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black, Contact surface: Tin, Mounting: THR soldering

## Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

### Accessories

Printed-circuit board connector - MC 1,5/ 4-GF-3,5 P26 THRR56 - 1789216

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black,  
Contact surface: Tin, Mounting: THR soldering



Printed-circuit board connector - MC 1,5/ 4-GF-3,5 P20 THRR56 - 1789436

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black,  
Contact surface: Tin, Mounting: THR soldering



Printed-circuit board connector - MC 1,5/ 4-GF-3,5 P14 THR - 1789643

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black,  
Contact surface: Tin, Mounting: THR soldering



Printed-circuit board connector - MC 1,5/ 4-GF-3,5 P14 THRR56 - 1789656

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black,  
Contact surface: Tin, Mounting: THR soldering



Base strip - MCV 1,5/ 4-GF-3,5 - 1843240

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: green,  
Contact surface: Tin, Mounting: Wave soldering



## Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

### Accessories

#### Base strip - MC 1,5/ 4-GF-3,5 - 1843813

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: green,  
Contact surface: Tin, Mounting: Wave soldering



#### Base strip - EMC 1,5/ 4-GF-3,5 - 1897267

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: green,  
Contact surface: Tin, Mounting: Press-in technology



#### Base strip - EMCV 1,5/ 4-GF-3,5 - 1911185

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: green,  
Contact surface: Tin, Mounting: Press-in technology



#### Base strip - MC 1,5/ 4-GF-3,5 THT - 1937334

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black,  
Contact surface: Tin, Mounting: THR soldering, User information and design recommendations for through hole  
reflow technology can be found under "Downloads"



#### Base strip - MCV 1,5/ 4-GF-3,5 THT - 1937428

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black,  
Contact surface: Tin, Mounting: THR soldering, User information and design recommendations for through hole  
reflow technology can be found under "Downloads"



## Printed-circuit board connector - MC 1,5/ 4-STF-3,5 - 1847071

### Accessories

Base strip - MC 1,5/ 4-GF-3,5 THT-R56 - 1996883



Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 3.5 mm, Color: black, Contact surface: Tin, Mounting: THR soldering, User information and design recommendations for through hole reflow technology can be found under "Downloads"