




Piezo Indicator

multicompPRO




DC Devices (with internal drive circuits)

Panel Mount - Screw Type

ABI-024-RC & ABI-025-RC



ABI-027-RC



Dimensions : Millimetres
Tolerance: $\pm 0.5\text{mm}$

Specifications




Part Number	ABI-024-RC	ABI-025-RC	ABI-027-RC
Rated Voltage	12V DC	12V DC	220V DC/AC
Operating Voltage	4 - 28V DC	6 - 28VDC	60 - 250V DC/AC
Rated Current	$\leq 8\text{mA}$	$\leq 6\text{mA}$	$\leq 16\text{mA}$
Sound Output level	$\geq 97\text{dB @30cm}$	$\geq 88\text{dB @30cm}$	$\geq 91\text{dB @30cm}$
Resonant Frequency	2800Hz $\pm 500\text{Hz}$	2900Hz $\pm 500\text{Hz}$	2800Hz $\pm 500\text{Hz}$
Tone	Continuous	Flat Pulse	Flat Pulse
Housing Material	Black ABS	Black ABS	Black ABS
Operating Temperature	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
Storage Temperature	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C
Weight	43g	43g	43g

Piezo Indicator


multicompPRO

Through Hole Type


ABI-001-RC



ABI-003-RC



ABI-007-RC



Dimensions : Millimetres
Tolerance: $\pm 0.5\text{mm}$


Specifications

Part Number	ABI-001-RC	ABI-003-RC	ABI-007-RC
Rated Voltage	12V DC	12V DC	12V DC
Operating Voltage	3 ~ 16V DC	3 ~ 20V DC	3 ~ 16V DC
Rated Current	$\leq 7\text{mA}$	$\leq 15\text{mA}$	$\leq 8\text{mA}$
Sound Output level	$\geq 80\text{dB @10cm}$	$\geq 95\text{dB @10cm}$	$\geq 90\text{dB @30cm}$
Resonant Frequency	4000Hz $\pm 500\text{Hz}$	3400Hz $\pm 500\text{Hz}$	3700Hz $\pm 500\text{Hz}$
Tone	Continuous		
Housing Material	Black Noryl		
Operating Temperature	-20°C to +70°C	-20°C to +60°C	
Storage Temperature	-30°C to +80°C	-30°C to +70°C	
Pin Pitch	7.6mm	15mm	15mm
Weight	1g	4g	5g


Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO


ABI-008-RC



ABI-033-RC



ABI-051-RC



Dimensions : Millimetres
Tolerance: $\pm 0.5\text{mm}$

Specifications


Part Number	ABI-008-RC	ABI-033-RC	ABI-051-RC
Rated Voltage	12V DC	24V DC	12V DC
Operating Voltage	3 ~ 20V DC	3 ~ 30V DC	3 ~ 20V DC
Rated Current	≤ 8mA	≤ 30mA	≤ 15mA
Sound Output level	≥ 85dB @30cm	≥ 95dB @10cm	≥ 95dB @10cm
Resonant Frequency	2900Hz ±500Hz	3400Hz ±500Hz	
Tone	Continuous		
Housing Material	Black Noryl		
Operating Temperature	-20℃ to +60℃	-20℃ to +70℃	-20℃ to +70℃
Storage Temperature	-30℃ to +70℃	-30℃ to +80℃	-40℃ to +85℃
Pin Pitch	15mm	17.5mm	17.5
Weight	6g	4g	4g

Piezo Indicator


multicompPRO

Flange Mount - Wire Lead Type


ABI-004-RC & ABI-005-RC



ABI-006-RC



ABI-014-RC



Dimensions : Millimetres
Tolerance: $\pm 0.5\text{mm}$


Specifications

Part Number	ABI-004-RC	ABI-005-RC	ABI-006-RC	ABI-014-RC
Rated Voltage	12V DC	24V DC	12V DC	12V DC
Operating Voltage	1.5 ~ 16VDC	1.5 ~ 28VDC	3 ~ 16VDC	3 ~ 30VDC
Rated Current	$\leq 15\text{mA}$	$\leq 20\text{mA}$	$\leq 8\text{mA}$	$\leq 3\text{mA}$
Sound Output level	$\geq 95\text{dB @30cm}$	$\geq 95\text{dB @30cm}$	$\geq 90\text{dB @30cm}$	$\geq 80\text{dB @30cm}$
Resonant Frequency	3500Hz $\pm 500\text{Hz}$	3500Hz $\pm 500\text{Hz}$	3700Hz $\pm 500\text{Hz}$	4500Hz $\pm 500\text{Hz}$
Tone	Continuous			
Housing Material	Black ABS			
Operating Temperature	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
Storage Temperature	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C
Lead Wire	UL1007 AWG26	UL1007 AWG26	UL1095 AWG28	UL1007 AWG26
Lead Length	100mm			
Weight	15g		5g	4g


Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO

ABI-023-RC



ABI-056-RC



Dimensions : Millimetres
Tolerance: $\pm 0.5\text{mm}$

Specifications

Part Number	ABI-023-RC	ABI-056-RC
Rated Voltage	12V DC	12V DC
Operating Voltage	3 ~ 20VDC	3 ~ 28VDC
Rated Current	$\leq 10\text{mA}$	$\leq 9\text{mA}$
Sound Output level	$\geq 96\text{dB @30cm}$	$\geq 90\text{dB @30cm}$
Resonant Frequency	2800Hz $\pm 500\text{Hz}$	2800Hz $\pm 500\text{Hz}$
Tone	Continuous	Slow Pulse 1.2 $\pm 30\%\text{Hz}$
Housing Material	Black ABS	Black ABS
Operating Temperature	-20°C to +60°C	-20°C to +60°C
Storage Temperature	-30°C to +70°C	-30°C to +70°C
Lead Wire	UL1007 AWG28	UL1007 AWG24
Lead Length	140mm	140mm
Weight	15g	15g

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.