

USB Type A To USB Type B Cable Assembly

multicompPRO

**RoHS
Compliant**



Specifications:

Material:

Connector:

Housing : Thermoplastic, Class fiber fill
Contact : Phosphor Bronze, Gold Plating over
Copper Underplating

Cable : USB standard Full Speed Type
Overmold : PVC

Electrical:

Voltage : 30V DC
Current : 1A Max. Per contact

Mechanical:

Random Vibration duration : No discontinuity of 1us or Longer
Physical shock duration : No discontinuity of 1us or Longer
Insertion Force : 4Kg Max.
Withdrawal Force : 1Kg to 4Kg


Environmental:

Thermal Shock : 10 Cycle -55°C and +85°C

Colour : Off White

WIRE DIAGRAM

TYPE A	Colour	TYPE B
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
SHELL	BRAID	SHELL



Dimensions : Inches (Millimeters)

Part Number Table

Description	Part Number
USB Type A To USB Type B Cable Assembly	SPC4799

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO