

0402SFF150F/24-2 Product Details

 Share Print Email



 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Type = DC Fast Acting Chip Fuse
- Surface Mount Construction
- Form Factor (inches) = 0402
- Form Factor (mm) = 1005
- Rated Current = 1.5 A

[View all Features](#)

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

TE Internal Number: E46629-000

 Active

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information	
Product Drawings: - None Available Catalog Pages/Data Sheets: CP CATALOG 2011-FUSES (PDF, English) Product Specifications: 0402SFF FAMILY (PDF, English) Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available	Related Products: Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Family Name = SFF Electrical Characteristics: - Rated Current (A) = 1.5 - Cold DCR (Nominal) (Ω) = 0.056 - Interrupt Voltage, Max. (VDC) = 24 - Interrupt Current, Max. (A) = 35 Termination Features: - Construction = Surface Mount Body Features: - Type = DC Fast Acting Chip Fuse Configuration Features: - Form Factor (inches) = 0402 - Form Factor (mm) = 1005	Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C - RoHS/ELV Compliance History = Always was RoHS compliant - UL Listed = File No. E197536 Environmental: - Operating Temperature (Max.) (°C) = 125 Conditions for Usage: - Min Clear Time @ 100% Rated Current (Hr) = 4 - Max Clear Time @ 250% Rated Current (Seconds) = 5 - Max Clear Time @ 400% Rated Current (Seconds) = 0.05 Other: - Brand = Raychem

