


Transient Voltage Suppression Diodes

P6KE Series, 600W

multicompPRO



Features

- Exceeds environmental standards of MIL-STD-19500
- 600W surge capability at $10 \times 1,000\mu\text{s}$ waveform, duty cycle: 0.01%
- Excellent clamping capability
- Low zener impedance
- Fast response time: typically less than 1ps from 0V to VBR for unidirectional and 5ns for bidirectional
- Typical IR less than $1\mu\text{A}$ above 10 V
- High temperature soldering guaranteed: 260°C / 10 seconds / 0.375 Inched (9.5mm) lead length/5lbs. (2.3kg) tension
- Case style: DO-204AC (DO-15) molded plastic

Mechanical Data

Case : Molded plastic

Lead : Pure tin plated lead free, solderable per MIL-STD-202, Method 208

Polarity : Colour band denotes cathode except bipolar

Weight : 0.42g

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.


Characteristics	Symbol	Values	Unit
Peak Power Dissipation at $T_A = 25^\circ\text{C}$, $T_P = 1\text{ms}$ (Note 1)	P_{PK}	Min. 600	Watts
Steady State Power Dissipation at $T_L = 75^\circ\text{C}$ Lead Lengths 0.375 Inch 9.5 mm (Note 2)	P_D	5	
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) (Note 3)	I_{FSM}	100	Amps
Maximum Instantaneous Forward Voltage at 50A for Unidirectional Only (Note 4)	V_F	3.5 / 5	Volts
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +175	$^\circ\text{C}$

Notes : 1. Non-repetitive current pulse ,per Fig. 5 and derated above $T_A = 25^\circ\text{C}$ per Fig. 1 .

2. 8.3ms single half-wave duty cycle = 4 pulses per minutes maximum (uni-directional units only).

3. $V_F = 3.5\text{V}$ on P6KE6.8 thru P6KE130 devices and $V_F = 5\text{V}$ on P6KE220A thru P6KE400A devices.

**RoHS
Compliant**



Ratings and Characteristic Curves

FIG.1-PULSE DERATING CURVE




FIG.2-TYPICAL JUNCTION CAPACITANCE




FIG.3-PULSE RATING CURVE




FIG.4-STEADY STATE POWER DERATING CURVE





FIG.5 -PULSE WAVE FORM



Transient Voltage Suppression Diodes

P6KE Series, 600W

multicompPRO

Electrical Characteristics (T_A = 25°C unless otherwise noted)

Part Number		Reverse Standoff Voltage	Breakdown Voltage BV Volts @ It			Max. Reverse Leakage @	Max. Clamping Voltage @IP	Max. Peak Pulse Current	Max. Voltage Temp. Variation of BV
Unidirectional	Bidirectional	VR(V)	Min. (V)	Max. (V)	It (mA)	IR(μA)	Vc(V)	Ipp(A)	% / °C
P6KE6.8A	P6KE6.8CA	5.8	6.45	7.14	10	1000	10.5	57	0.057
P6KE43A	P6KE43CA	36.8	40.9	45.2	1	5	59.3	10.1	0.101
-	P6KE56CA	47.8	53.2	58.8	1	5	77	7.8	0.103
P6KE130A	P6KE130CA	111	124	137	1	5	179	3.3	0.107

Notes:

Suffix 'C' denotes bidirectional device . Suffix 'A' denotes 5% tolerance device. No suffix denotes 10% tolerance device.

1. For bidirectional devices having VR of 10volts and under ,the IR limit is doubled .

Part Number Table

Description	Part Number
TVS Diode, 600W, 6.8V _{BR} Nom, Unidirectional, DO-204AC (DO-15)	P6KE6.8A
TVS Diode, 600W, 6.8V _{BR} Nom, Bidirectional, DO-204AC (DO-15)	P6KE6.8CA
TVS Diode, 600W, 43V _{BR} Nom, Unidirectional, DO-204AC (DO-15)	P6KE43A
TVS Diode, 600W, 43V _{BR} Nom, Bidirectional, DO-204AC (DO-15)	P6KE43CA
TVS Diode, 600W, 56V _{BR} Nom, Bidirectional, DO-204AC (DO-15)	P6KE56CA
TVS Diode, 600W, 130V _{BR} Nom, Unidirectional, DO-204AC (DO-15)	P6KE130A
TVS Diode, 600W, 130V _{BR} Nom, Bidirectional, DO-204AC (DO-15)	P6KE130CA

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicompPRO