



Features

- High surge capacity.
- Low power loss high efficiency.
- Glass passivated chip junctions.
- 150°C operating junction temperature.
- Low stored charge majority carrier conduction.
- Low forward voltage, high current capability.
- High-switching speed 50 nanosecond recovery time.
- Plastic material used carries Underwriters Laboratory
- Flammability classification 94V-0

Specifications

Reverse Voltage : 400 and 600 Volts

Forward Current : 30 Amperes


Maximum Ratings

Characteristic	Symbol	MUR1540	MUR1560	Units
Peak Repetitive Reverse Voltage	V_{RRM}	400	600	V
Working Peak Reverse Voltage	V_{RWM}			
DC Blocking Voltage	V_R			
RMS Reverse Voltage	$V_{R(RMS)}$	280	420	
Average Rectifier Forward Current	$I_{F(AV)}$	15		A
Peak Repetitive Forward Current (Rate V_R , Square Wave, 20kHz)	I_{FM}	20		
Non-Repetitive Peak Surge Current (Surge applied at rate load conditions half-wave, single phase, 60Hz)	I_{FSM}	225		
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-65 to +150		
				°C


Electrical Characteristics

Characteristic	Symbol	MUR1540	MUR1560	Units
Maximum Instantaneous Forward Voltage ($I_F = 15$ Amperes $T_C = 25^\circ\text{C}$) ($I_F = 15$ Amperes $T_C = 125^\circ\text{C}$)	V_F	1.3 1.16	1.5 1.37	V
Maximum Instantaneous Reverse Current (Rated DC Voltage, $T_C = 25^\circ\text{C}$) (Rated DC Voltage, $T_C = 125^\circ\text{C}$)	I_R	10 700		mA
Reverse Recovery Time ($I_F = 0.5\text{A}$, $I_R = 1\text{A}$, $I_{RR} = 0.25\text{A}$)	T_{RR}	50		ns
Typical Junction Capacitance (Reverse Voltage of 4 Volts and $f = 1\text{MHz}$)	C_P	150	120	pF


Typical Forward Characteristics




Forward Current Derating Curve




Typical Reverse Characteristics





Typical Junction Capacitance



Peak Forward Surge Current





Set time base for 10/20 ns/div


Reverse Recovery Time Characteristic and Test Circuit Diagram

Notes:

1. Rise Time = 7ns maximum input impedance = 1MΩ, 22pF.
2. Rise Time = 10ns maximum input impedance = 50Ω

Diagram

TO-220A



Dim.	Min.	Max.
A	14.68	15.32
B	9.78	10.42
C	6.01	6.52
D	13.06	14.62
E	3.57	4.07
F	4.83	5.33
G	1.12	1.36
H	0.72	0.96

Dim.	Min.	Max.
I	4.22	4.98
J	1.14	1.36
K	2.20	2.97
L	0.33	0.55
M	2.48	2.98
N	-	1
O	3.7	3.9

Dimensions : Millimetres

Common Cathode



Part Number Table

Description	Part Number
Ultra Fast Rectifiers, 400V	MUR1540
Ultra Fast Rectifiers, 600V	MUR1560

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.