




**RoHS
Compliant**



Pin Configuration

1. Base
2. Collector
3. Emitter
4. Collector

Description:

A silicon Darlington transistor in a TO-220 case intended for general purpose amplifier and low speed switching applications.


Absolute Maximum Ratings:

Collector-Base Voltage, V_{CBO}	: 80V
Collector-Emitter Voltage, V_{CEO}	: 80V
Collector Current, I_C	: DC: 8A Pulse: 15A
Base Current, I_B	: 1A
Collector Dissipation ($T_C = +25^\circ\text{C}$), P_C	: 80W
Operating Junction Temperature, T_J	: $+150^\circ\text{C}$
Storage Temperature Range, T_{stg}	: -65°C to $+150^\circ\text{C}$
Thermal Resistance, Junction-to-Case, R_{thJC}	: 1.56°C/W

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min.	Typ	Max.	Unit
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 30\text{mA}$, $I_B = 0$, Note 1	80	-	-	V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = 80\text{V}$, $I_E = 0$	-	-	50	μA
	I_{CEO}	$V_{CE} = 40\text{V}$, $I_B = 0$	-	-	50	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB} = 5\text{V}$, $I_C = 0$	-	-	8	mA
DC Current Gain	h_{FE}	$I_C = 3\text{A}$, $V_{CE} = 4\text{V}$	1,000	-	20,000	-
		$I_C = 8\text{A}$, $V_{CE} = 4\text{V}$	200	-	-	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 3\text{A}$, $I_B = 6\text{mA}$, Note 1	-	-	2	V
		$I_C = 8\text{A}$, $I_B = 80\text{mA}$, Note 1	-	-	2.5	
Base-Emitter Saturation Voltage	$V_{BE(on)}$	$I_C = 8\text{A}$, $I_B = 4\text{V}$, Note 1	-	-	2.8	
Small-Signal Current Gain	h_{fe}	$I_C = 3\text{A}$, $V_{CE} = 4\text{V}$, $f = 1\text{MHz}$	4	-	-	-

Note 1. Pulse Test: Pulse Width = 300 μs , Duty Cycle = 1.5%.



Pin Configuration

1. Base
2. Collector
3. Emitter
4. Collector

Dim.	Min.	Max.
A	14.42	16.51
B	9.63	10.67
C	3.56	4.83
D	-	0.9
E	1.15	1.4
F	3.75	3.88
G	2.29	2.79
H	2.54	3.43
J	-	0.56
K	12.7	14.73
L	2.8	4.07
M	2.03	2.92
N	-	31.24
O	7°	7°

Dimensions : Millimetres

Part Number Table

Description	Part Number
Transistor, NPN, 8A, 80V, TO-220	TIP101

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.