

"High Frequency Ceramic Solutions"

2.45 GHz High Gain Chip Antenna (Vertical Orientation)

P/N 2450AT45A100

Detail Specification: 01/05/2012

Page 1 of 10


General Specifications

Part Number	2450AT45A100
Frequency Range	2400 - 2500 Mhz
Peak Gain	3.0 dBi typ. (XZ-V)
Average Gain	1.0 dBi typ. (XZ-V)
Return Loss	9.5 dB min.

Input Power	3W max.
Impedance	50 Ω
Operating Temperature	-40 to +85°C
Reel Quantity	1,000

Mechanical Dimensions

	In	mm
L	0.374 $\pm$ 0.008	9.50 $\pm$ 0.20
W	0.079 $\pm$ 0.008	2.00 $\pm$ 0.20
T	0.047 $\pm$ 0.004/-0.008	1.20 $\pm$ 0.1/-0.2
a	0.020 $\pm$ 0.012	0.50 $\pm$ 0.30




Terminal Configuration

No.	Function
1	Feeding Point
2	NC


Mounting Considerations 1

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50 Ω impedance matching characteristics.



a) Without Matching Circuit (moderate bandwidth)



b) With Matching Circuit* (wide bandwidth)

* matching circuit and component values will depend and vary on PCB layout, thickness, material, etc.

EVB p/n:
2450AT45A100-EB1SMA

JTI P/N for Matching Circuit:
Cap (1.5pF): 500R07S1R5BV4T
Inductor (3.9nH): L-07C3N9SV6T

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain Chip Antenna (Vertical Orientation)

P/N 2450AT45A100


Detail Specification: 01/05/2012

Page 2 of 10

Typical Electrical Characteristics (T=25°C)



Test Board

EVB p/n:
2450AT45A100-EB1SMA





Return Loss

a) Without Matching Circuit



a) With Matching Circuit



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"


2.45 GHz High Gain Chip Antenna (Vertical Orientation)

Detail Specification: 01/05/2012

P/N 2450AT45A100

Page 3 of 10

Typical Radiation Patterns



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain Chip Antenna (Horizontal Orientation_1)

P/N 2450AT45A100

Detail Specification: 01/05/2012


Page 4 of 10

General Specifications

Part Number	2450AT45A100
Frequency Range	2400 - 2500 Mhz
Peak Gain	1.5 dBi typ. (XZ-V)
Average Gain	0.0 dBi typ. (XZ-V)
Return Loss	9.5 dB min.


Mechanical Dimensions

	In	mm
L	0.374 ± 0.008	9.50 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
T	0.047 +.004/-.008	1.20 +0.1/-0.2
a	0.020 ± 0.012	0.50 ± 0.30



Terminal Configuration


No.	Function
1	Feeding Point
2	NC



Mounting Considerations 2

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50 Ω impedance matching characteristics.



EVB p/n:
2450AT45A100-EB2SMA

Units in mm

* matching circuit and component values will depend on PCB layout, thickness, material, etc.

JTI P/N for Matching Circuit:
Cap (1.5pF): 500R07S1R5BV4T

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz High Gain Chip Antenna (Horizontal Orientation_1)

P/N 2450AT45A100

Detail Specification: 01/05/2012

Page 5 of 10




Typical Electrical Characteristics (T=25°C)

Test Board

EVB p/n:
2450AT45A100-EB2SMA

Return Loss

a) With Matching Circuit



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"


2.45 GHz High Gain Chip Antenna (Horizontal Orientation_1)

P/N 2450AT45A100



Detail Specification: 01/05/2012

Page 6 of 10



Typical Radiation Patterns




XY cut @2.45GHz
 — Vertical
 Horizontal



XZ cut @2.45GHz
 — Vertical
 Horizontal



YZ cut @2.45GHz
 — Vertical
 Horizontal



Johanson Technology, Inc. reserves the right to make design changes without notice.
 All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation_2)

P/N 2450AT45A100

Detail Specification: 01/05/2012


Page 7 of 10

General Specifications

Part Number	2450AT45A100
Frequency Range	2400 - 2500 Mhz
Peak Gain	1.3 dBi typ. (XZ-V)
Average Gain	0.6 dBi typ. (XZ-V)
Return Loss	9.5 dB min.


Mechanical Dimensions

	In	mm
L	0.374 ± 0.008	9.50 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
T	0.047 +.004/-.008	1.20 +0.1/-0.2
a	0.020 ± 0.012	0.50 ± 0.30



Terminal Configuration


No.	Function
1	Feeding Point
2	NC



Mounting Considerations 3

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50 Ω impedance matching characteristics.



Units in mm

* matching circuit and component values will depend on PCB layout, thickness, material, etc.

EVB p/n:
2450AT45A100-EB3SMA

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation_2)

P/N 2450AT45A100

Detail Specification: 01/05/2012

Page 8 of 10

Typical Electrical Characteristics (T=25°C)




Test Board

EVB p/n:

2450AT45A100-EB3SMA

Return Loss

a) With Matching Circuit



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"


2.45 GHz Antenna (Horizontal Orientation_2)

Detail Specification: 01/05/2012

P/N 2450AT45A100

Page 9 of 10

Typical Radiation Patterns



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com
4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz Antenna

P/N 2450AT45A100

Detail Specification: 01/05/2012

Page 10 of 10

Ordering Information

Packaging Style*	Bulk (loose pieces)	Suffix = S	Eg. 2450AT45A100S
	T & R	Suffix = E	Eg. 2450AT45A100E
	T & R (Reverse)	Suffix = R	Eg. 2450AT45A100R
Termination Style	100% Tin	Suffix = None	Eg. 2450AT45A100(S, E, R)
	Tin / Lead	Please consult Factory	
Evaluation Boards (1-port SMA antenna test boards)	2450AT45A100-EB1SMA (Page 2)		
	2450AT45A100-EB2SMA (Page 5)		
	2450AT45A100-EB3SMA (Page 8)		

*<http://johansontechnology.com/en/integrated-passives/integrated-passive-tape-a-reel-packaging.html>

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2012 Johanson Technology, Inc. All Rights Reserved