



Main

Range	Legacy
Product Type	Solid state relay
Nominal Output Current	15 A DC
Network Number of Phases	1 phase
Mounting Support	Panel DIN rail
Output Voltage	3...50 V DC
Control Circuit Voltage	3.5...32 V DC

Complementary

Holding Current	20 mA
Input Current Limits	12 mA 5 V DC typical
Switch Function	SPST
Contacts Type and Composition	NO
Protection Technology	Current limiter
Protection Type	Reverse polarity protection
Tightening Torque	0.8 N.m input/output
Connections Terminals	Input/output screw clamp terminal 0.00 in ² (2.5 mm ²) AWG 14)
Local Signalling	Input status 1 LED green)
Switching Device	Mosfet output DC switching
Load Current	15 A at nominal load
Overload Current	24 A for 1 second
Surge Current	50 A 1 cycle
Must Release Voltage	1 V
Voltage Drop	<0.5 V on-state DC
Resistance	0.04 Ohm on-state
Thermal Resistance	1.4 °C/W
Leakage Current	0.1 mA at off-state 50 V DC
Response Time	5 ms turn-off) 5 ms turn-on)
Dielectric Strength	2500 V between input and output 2500 V between terminals and chassis
Height	2.56 in (65 mm)
Width	0.62 in (15.75 mm)
Depth	3.54 in (89.83 mm)
Product Weight	4.48 oz (127.1 g)
Device Presentation	Complete device

Environment

Product Certifications	CE CSA UL
IP Degree of Protection	IP20
Ambient Air Temperature for Operation	-22...176 °F (-30...80 °C)
Ambient Air Temperature for Storage	-40...212 °F (-40...100 °C)


Ordering and shipping details

GTIN	03606480282195
------	----------------

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Approximate Dimensions



Connections and Wiring Diagrams

