

Printview: Male connector; for DIN 35 rail mounting; 7-pole; pin spacing 7.62 mm / 0.3 in; 100% protected against mismating; codable - Item No.: 831-3207/007-000

WAGO® online catalog / eShop

Male connector; for DIN 35 rail mounting; 7-pole; pin spacing 7.62 mm / 0.3 in; 100% protected against mismating; codable

Item No.: 831-3207/007-000



Male connector; for DIN 35 rail mounting; 7-pole; pin spacing 7.62 mm / 0.3 in; 100% protected against mismating; codable

Marking

RoHS ✓
Compliant

Business data

Supplier	WAGO
Item no.	831-3207/007-000
GTIN / EAN	4045454333812
Content	1
Order amount	12
Customer item number	

Notes

Universal connection for all conductor typesSimple push-in of both solid and ferruled conductorsIntegrated test ports for 2mm Ø test plugs600V to UL 1059 100% protected against mismatingCoding option available

Technical data

Miscellaneous

No. of poles	7
Pin Spacing	7.62 mm (0.3 in %)
Total number of connection points	7
Total number of potentials	7
Color	light gray
Ratings according to 1	IEC/EN 60664-1
Overvoltage category EN 1	III

Technical data	
Pollution degree (1)	2
Rated voltage EN (1) [V]	1000 [V]
Rated surge voltage (1) [kV]	8 [kV]
Nominal current [A]	41 [A]
Overvoltage category EN 2	II
Degree of pollution (2)	2
Rated voltage EN (2) [V]	1000 [V]
Rated surge voltage (2) [kV]	8 [kV]
Nominal current (2) [A]	41 [A]
Overvoltage category EN 3	III
Degree of pollution (3)	3
Rated voltage EN (3) [V]	800 [V]
Rated surge voltage (3) [kV]	8 [kV]
Nominal current (3) [A]	41 [A]
Number of individual connection objects at the product	1
Connection technology (1)	Push-in CAGE CLAMP®
Solid sizes 1	0.5 ... 10 mm ² / 20 ... 8 AWG
Fine-stranded wires 1	0.5 ... 10 mm ² / 20 ... 8 AWG
Fine-stranded wires with insulated ferrule 1	0.5 ... 6 mm ² / ...
Fine-stranded wires with uninsulated ferrule 1	0.5 ... 6 mm ² / ...
Strip length 1	13 ... 15 mm / 0.51 ... 0.59 in
Connection type	Quick-connect/Solder contact
Type of wiring	Side-entry wiring
Material group	I
Insulating material	Polyamide 66 (PA 66)
Flammability rating per UL 94	V0
Limit temperature range	-60 C ... 105 C
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (Ecu)
Contact plating	tin-plated
Fire load [MJ]	0.929 [MJ]
Weight [g]	49.1 [g]
Width	55.22 mm / 2.174 in
Height	39 mm / 1.535 in


Printview: Male connector; for DIN 35 rail mounting; 7-pole; pin spacing 7.62 mm / 0.3 in; 100% protected against mismatching; codable - Item No.: 831-3207/007-000


Technical data

<i>Height from upper-edge of DIN-rail [mm]</i>	<i>34 [mm]</i>
<i>Height from upper-edge of DIN-rail</i>	<i>34 mm / 1.339 in</i>
<i>Length</i>	<i>46 mm / 1.811 in</i>

Printview: Male connector; for DIN 35 rail mounting; 7-pole; pin spacing 7.62 mm / 0.3 in; 100% protected against mismatching; codable - Item No.: 831-3207/007-000

Images & drawings





Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.