


Part Number : MPSB 130/30

Proximity Switch - Reed Switch based

Rectangular - Normally Closed Contacts - Suggested Magnet: MPSM

Product Data Sheet

PICTURE	DIMENSIONS	Applications Include
	 Drawings not to scale All dimensions in mm(inches) nominal	• Position and limit sensing. • Linear actuators . • Security system switch. • Door Switch.
✓RoHS Compliant		Options • Also available in all Black. • White economy version available. • Left and Right hand version available. • Custom cable lengths, strip lengths, cable types, terminations. • If you do not see what you need, just ask, as there is a strong possibility we can do it !

SPECIFICATION	
Contact Form / Style	Normally Closed
Switching Capacity (Resistive)	5 W/VA Max.
Switching Voltage	100 VAC Max.
Switching Current	0.5 A. Max.
Carry Current	1.0 A. Max.
Breakdown Voltage	200 VDC Min.
Contact Resistance	150 mOhms Max.
Switching Distance	8 mm Min.
Operating Temperature Range	-40°C +105°C
Storage temperature	-25°C +90°C
Case Material	Glass Filled Nylon
Cable	2 x Round 0.25mm ² Irradiated PVC insulated Grey

Did you know we also sell?









Float Switches Magnets Movement Sensors Tilt / Tip Switches Acceleration / Shock Switches Reed Relays Solid State Relays

Rev. No.	Revision Note	Date	Signature
3	Datasheet Redesign	14-02-11	ML