

CM5740Z171B-10




**UNCONTROLLED
DOCUMENT**

PHYSICAL DIMENSIONS:

A	14.48 [.570]	+ 0.23 [.009]
B	10.03 [.395]	+ 0.15 [.006]
C	9.32 [.367]	+ 0.15 [.006]
C ₁	12.90 [.508]	MAX.
D	4.06 [.160]	+ 0.13 [.005]
E	2.54 [.100]	+ 0.13 [.005]
E ₁	3.43 [.135]	+ 0.13 [.005]

WIRE:

T ₁	3.12 [.123]	+ 0.25 [.010]
T ₂	0.76 [.030]	TYP.
T ₃	0.76 [.030]	TYP.




ELECTRICAL CHARACTERISTICS:

Z @ 100MHz (Ω)	DCR (Ω)	Rated Current	Rated Voltage (VDC)
Nominal	170		
Minimum	128		
Maximum	—	0.001	20,000 mA
			290



NOTES: UNLESS OTHERWISE SPECIFIED

1. BULK PACKAGED, 825 PCS PER CASE.
2. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
3. TERMINATION FINISH IS 100% TIN.
4. THIS PART HAS NO PIN POLARITY.
5. OPERATION TEMPERATURE (INCLUDING SELF-HEATING):
-40 ~ +125°C.


HOLE PATTERNS FOR WAVE SOLDERING




DIMENSIONS ARE IN mm (INCHES).				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
D	ADD RATED VOLTAGE AND NOTE 5	08/30/12	QIU				
C	UPDATE COMPANY LOGO & KAPTON LABEL	11/13/08	JRK				
B	CHG ISO VIEW UPDATE COMPANY LOGO	06/15/07	JRK				
A	ORIGINAL DRAFT	6/11/04	JRK				
REV	DESCRIPTION	DATE	INT	PROJECT/PART NUMBER: CM5740Z171B-10 DATE: 6/11/04 CAD # CM5740Z171B-10-D-2			
				REV	D	PART TYPE: ASSEMBLY	DRAWN BY: JRK
				SCALE:	NTS	SHEET:	2 of 3
				TOOL #	HQ570		




SECTION A-A



0.10 (.004)
SEATING PLANE
(CO-PLANARITY)



**UNCONTROLLED
DOCUMENT**



ELECTRICAL TESTING

	GROSS	GROSS
TEST:	Z	Z
# TURNS	1	1
AWG	22	22
FREQUENCY	25 MHz	100 MHz
NOMINAL	- Ω	170 Ω
MINIMUM	- Ω	128 Ω
WEIGHT/1000	5.85 kgs.	12.89lbs.



DIMENSIONS:

A	14.48 [.570]	+	0.23 [.009]
B	10.03 [.395]	+	0.15 [.006]
C	9.32 [.367]	+	0.15 [.006]
C1	12.90 [.508]		MAX.
D	4.06 [.160]	+	0.13 [.005]
E	2.54 [.100]	+	0.13 [.005]
E1	3.43 [.135]	+	0.13 [.005]

WIRE DIMENSIONS:

T1	3.12 [.123]	+	0.25 [.010]
T2	0.76 [.030]		TYP.
T3	0.76 [.030]		TYP.

NOTES: UNLESS OTHERWISE SPECIFIED

1. WIRE: REFERENCE STEWARD WIRE PURCHASE SPEC. W0040-61.
2. IMPEDANCE VALUES ARE GROSS, MEASURED USING W0040-61 WIRE PLACED AGAINST END OF SLOT w/ NO D.C. BIAS.
3. REFERENCE STEWARD CORE 24H0570-600.
4. TERMINATION FINISH IS 100% TIN.
5. THIS PART HAS NO PIN POLARITY.

DIMENSIONS ARE IN mm (INCHES).				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
D	ADD RATED VOLTAGE AND NOTE 5	08/30/12	QIU				
C	UPDATE COMPANY LOGO & KAPTON LABEL	11/13/08	JRK				
B	CHG ISO VIEW UPDATE COMPANY LOGO	06/15/07	JRK				
A	ORIGINAL DRAFT	6/11/04	JRK				
REV	DESCRIPTION	DATE	INT				
				PROJECT/PART NUMBER:		REV	PART TYPE:
				CM5740Z171B-10		D	ASSEMBLY
				DATE: 6/11/04		SCALE: NTS	SHEET: 2 of 3
				CAD # CM5740Z171B-10-D-2		TOOL # H0570	