


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
J	ECN 7195: REVISE 3D MODEL TO VENDOR, ROHS, FORMAT	12/11/13	D.FRISIELLO



MODEL NUMBER	LENGTH METERS [FEET]
UPMAA-03M	0.3 [.98]
UPMAA-05M	0.5 [1.64]
UPMAA-075M	0.75 [2.46]
UPMAA-1M	1.0 [3.28]
UPMAA-2M	2.0 [6.56]
UPMAA-3M	3.0 [9.84]
UPMAA-4M	4.0 [13.12]
UPMAA-5M	5.0 [16.41]

NOTES:

- CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
- CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- MOUNTING HARDWARE INCLUDED: 2X #4-40 X .38 LG. PHILLIPS HD SCREW
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [1.51] .XXX = ±.005 [1.3] PROJECTION 	APPROVALS	DATE	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	DRAWN BY D.FRISIELLO	4/18/08		
	CHECKED BY D.FORTIN	4/18/08	CATEGORY USB	
	APPROVED BY S.SMITH	4/18/08	PRODUCT DESCRIPTION CA USB-A PNL/USB-AM	
COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321	DWG. NO. UPMAA	REV. J
	SCALE: NONE	CAD FILE: UPMAA.SLDDRW	SHEET 1 OF 1	