

# Printed-circuit board connector - DMCV 1,5/ 6-G1F-3,5-LR P20THR - 1787438

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 8 A, Rated voltage (III/2): 160 V, Number of positions: 6, Pitch: 3.5 mm, Color: black, Contact surface: Tin, Mounting: THR soldering



The figure shows a 10-pos. version with 20 contacts

## Why buy this product

- ✓ Designed for integration into the SMT soldering process
- ✓ Vertical connection enables multi-row arrangement on the PCB
- ✓ Screwable flange for superior mechanical stability
- ✓ Automatic locking and intuitive release through Lock and Release operating lever in contrasting color
- ✓ Small component size for applications where space is at a premium



## Key Commercial Data

|                                      |                                                                                      |
|--------------------------------------|--------------------------------------------------------------------------------------|
| Packing unit                         | 50 STK                                                                               |
| GTIN                                 |  |
| GTIN                                 | 4046356597050                                                                        |
| Weight per Piece (excluding packing) | 3.330 g                                                                              |
| Custom tariff number                 | 85366990                                                                             |
| Country of origin                    | Germany                                                                              |

## Technical data

### Dimensions

|                       |         |
|-----------------------|---------|
| Length                | 10.6 mm |
| Pitch                 | 3.5 mm  |
| Dimension a           | 17.5 mm |
| Width                 | 28 mm   |
| Constructional height | 10 mm   |
| Height                | 12 mm   |

# Printed-circuit board connector - DMCV 1,5/ 6-G1F-3,5-LR P20THR - 1787438

## Technical data

### Dimensions

|                          |           |
|--------------------------|-----------|
| Length of the solder pin | 2 mm      |
| Pin dimensions           | 0,8 x 0,8 |
| Pin spacing              | 5.50 mm   |
| Hole diameter            | 1.4 mm    |

### General

|                                        |                      |
|----------------------------------------|----------------------|
| Range of articles                      | DMCV 1,5/...-G1F-THR |
| Insulating material group              | IIIa                 |
| Rated surge voltage (III/3)            | 2.5 kV               |
| Rated surge voltage (III/2)            | 2.5 kV               |
| Rated surge voltage (II/2)             | 2.5 kV               |
| Rated voltage (III/3)                  | 160 V                |
| Rated voltage (III/2)                  | 160 V                |
| Rated voltage (II/2)                   | 250 V                |
| Connection in acc. with standard       | EN-VDE               |
| Nominal current $I_N$                  | 8 A                  |
| Maximum load current                   | 8 A                  |
| Insulating material                    | LCP                  |
| Flammability rating according to UL 94 | V0                   |
| Color                                  | black                |
| Number of positions                    | 6                    |

### Standards and Regulations

|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CUL    |
| Flammability rating according to UL 94 | V0     |


### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |


## Drawings

# Printed-circuit board connector - DMCV 1,5/ 6-G1F-3,5-LR P20THR - 1787438

Schematic diagram




Drilling diagram




Use of the CP-DMC... coding profile

Dimensional drawing



Schematic diagram



Panel cutout

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |
| eCl@ss 9.0 | 27440402 |

ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |
| ETIM 6.0 | EC002637 |

UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 6.01 | 30211810 |
|-------------|----------|

# Printed-circuit board connector - DMCV 1,5/ 6-G1F-3,5-LR P20THR - 1787438

## Classifications

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Approvals

### Approvals

#### Approvals

VDE Gutachten mit Fertigungsüberwachung / IECEE CB Scheme / cULus Recognized / EAC

#### Ex Approvals

### Approval details

|                                            |                                                                                     |                                                                                                                                                                                                              |          |
|--------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx">http://www.vde.com/en/Institute/OnlineService/<br/>VDE-approved-products/Pages/Online-Search.aspx</a> | 40038423 |
| Nominal current I <sub>N</sub>             | 8 A                                                                                 |                                                                                                                                                                                                              |          |
| Nominal voltage U <sub>N</sub>             | 160 V                                                                               |                                                                                                                                                                                                              |          |

|                                |                                                                                     |                                                           |                 |
|--------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|-----------------|
| IECEE CB Scheme                |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-56070_B1_B2 |
| Nominal current I <sub>N</sub> | 8 A                                                                                 |                                                           |                 |
| Nominal voltage U <sub>N</sub> | 160 V                                                                               |                                                           |                 |

|                                |                                                                                     |                                                                                                                                                       |                 |
|--------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized               |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20110128 |
|                                | B                                                                                   | C                                                                                                                                                     |                 |
| Nominal current I <sub>N</sub> | 8 A                                                                                 | 8 A                                                                                                                                                   |                 |
| Nominal voltage U <sub>N</sub> | 150 V                                                                               | 50 V                                                                                                                                                  |                 |

## Printed-circuit board connector - DMCV 1,5/ 6-G1F-3,5-LR P20THR - 1787438

### Approvals

|     |                                                                                   |         |
|-----|-----------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-----------------------------------------------------------------------------------|---------|

### Accessories

#### Accessories

#### Coding element


Coding profile - CP-DMC 1,5 NAT - 1790647



Coding profile, for insertion between the coding ribs of the connector and the header following the reflow soldering process, insulating material, color: natural

### Additional products

Printed-circuit board connector - DFMC 1,5/ 6-STF-3,5 - 1790331



Plug, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 6 with 12 contacts, pitch: 3.5 mm, connection method: spring-cage connection, color: green, contact surface: tin

Printed-circuit board connector - DFMC 1,5/ 6-ST-3,5-LR - 1790522



Plug, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 6 with 12 contacts, pitch: 3.5 mm, connection method: spring-cage connection, color: green, contact surface: tin