

PCB TERMINAL BLOCKS

5mm Pitch Standard Profile 90° Screw Terminal

- 2 & 3 pole interlocking
- 2-12 pole solid block end stackable
- Guided pin alignment
- Moulded in grey UL94-V0 flame retardant PC
- Wire protector terminals
- 0.5-4.0mm² (30-14AWG) solid cable
- 0.5-2.5mm² (30-14AWG) stranded cable
- Anti solder wicking terminals
-  approved


CTB1050



TYPE NO.	POLES	LENGTH
CTB1050/2	2	10mm
CTB1050/3	3	15mm
CTB1050/4	4	20mm
CTB1050/5	5	25mm
CTB1050/6	6	30mm
CTB1050/7	7	35mm
CTB1050/8	8	40mm
CTB1050/9	9	45mm
CTB1050/10	10	50mm
CTB1050/11	11	55mm
CTB1050/12	12	60mm


SPECIFICATION

Rating	24A/250V UL=16A/300V, VDE&IMQ=24A/450V
Dielectric strength	≥2.5kV
Impulse withstand voltage	4kV
Working temperature	85°C
Moulding	UL94-V0 flame retardant PC
Pin/terminal	Tinned, nickel plated brass
Rising clamp	Nickel plated brass
Screw/torque	M3 steel zinc plated, 0.5Nm
Recommended PCB hole size	ø1.1mm




For other dimensions see CTB1000

5mm Pitch Commercial Standard Profile Screw Terminal

- 2-12 pole solid block
- End stackable
- Moulded in grey UL94-V0 flame retardant PC
- Wire protector terminals
- 0.5-4.0mm² (30-12AWG) solid cable
- 0.5-2.5mm² (30-12AWG) stranded cable
- Captive screw
- Anti solder wicking terminal
- Guided pin alignment
- 13 & 14 pole available on request
-  approved

CTB1500



TYPE NO.	POLES	LENGTH
CTB1500/2	2	10mm
CTB1500/3	3	15mm
CTB1500/4	4	20mm
CTB1500/5	5	25mm
CTB1500/6	6	30mm
CTB1500/7	7	35mm
CTB1500/8	8	40mm
CTB1500/9	9	45mm
CTB1500/10	10	50mm
CTB1500/11	11	55mm
CTB1500/12	12	60mm

SPECIFICATION

Rating	24A/250V UL=18A/300V, VDE&IMQ=24A/250V
Dielectric strength	≥2kV
Impulse withstand voltage	4kV
Working temperature	85°C
Moulding	UL94-V0 flame retardant PC
Pin/terminal	Tinned, nickel plated brass
Wire protector	Nickel plated brass
Screw/torque	M2.5 steel zinc plated, 0.5Nm
Recommended PCB hole size	ø1.1mm

