

## Single relay - REL-MR- 24DC/21HC - 2961312

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in miniature power relay, with power contact for high continuous currents, 1 PDT, input voltage 24 V DC

### Why buy this product

- ✓ Switching current of up to 16 A

RoHS

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 STK                                                                                                  |
| Minimum order quantity               | 10 STK                                                                                                  |
| GTIN                                 | <br>4 017918 187576 |
| GTIN                                 | 4017918187576                                                                                           |
| Weight per Piece (excluding packing) | 17.000 g                                                                                                |
| Custom tariff number                 | 85364190                                                                                                |
| Country of origin                    | Austria                                                                                                 |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Width  | 12.7 mm |
| Height | 29 mm   |
| Depth  | 15.7 mm |

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -40 °C ... 85 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

#### Coil side

|                                |         |
|--------------------------------|---------|
| Nominal input voltage $U_N$    | 24 V DC |
| Typical input current at $U_N$ | 17 mA   |
| Typical response time          | 7 ms    |

# Single relay - REL-MR- 24DC/21HC - 2961312

## Technical data

### Coil side

|                                         |                                     |
|-----------------------------------------|-------------------------------------|
| Typical release time                    | 3 ms                                |
| Coil resistance                         | 1440 $\Omega$ $\pm$ 10 % (at 20 °C) |
| Power dissipation for nominal condition | 0.41 W                              |

### Contact side

|                                                        |                        |
|--------------------------------------------------------|------------------------|
| Contact type                                           | 1 PDT                  |
| Type of switch contact                                 | Single contact         |
| Contact material                                       | AgNi                   |
| Maximum switching voltage                              | 250 V AC/DC            |
| Minimum switching voltage                              | 12 V (at 10 mA)        |
| Min. switching current                                 | 10 mA (at 12 V)        |
| Maximum inrush current                                 | 50 A (20 ms)           |
| Limiting continuous current                            | 16 A                   |
| Interrupting rating (ohmic load) max.                  | 384 W (at 24 V DC)     |
|                                                        | 58 W (at 48 V DC)      |
|                                                        | 48 W (at 60 V DC)      |
|                                                        | 50 W (at 110 V DC)     |
|                                                        | 80 W (at 220 V DC)     |
|                                                        | 4000 VA (for 250 V AC) |
| Switching capacity in acc. with DIN VDE 0660/IEC 60947 | 2 A (at 24 V, DC13)    |
|                                                        | 0.2 A (at 110 V, DC13) |
|                                                        | 0.2 A (at 250 V, DC13) |
|                                                        | 6 A (at 24 V, AC15)    |
|                                                        | 6 A (at 120 V, AC15)   |
|                                                        | 6 A (at 250 V, AC15)   |

### General

|                                          |                                                        |
|------------------------------------------|--------------------------------------------------------|
| Test voltage relay winding/relay contact | 5 kV AC (50 Hz, 1 min.)                                |
| Operating mode                           | 100% operating factor                                  |
| Degree of protection                     | RT II (flux-proof)                                     |
| Mechanical service life                  | 3 x 10 <sup>7</sup> cycles                             |
| Mounting position                        | any                                                    |
| Assembly instructions                    | Can be aligned without spacing (> 70 °C $\geq$ 2.5 mm) |

### Standards and Regulations

|                                  |            |
|----------------------------------|------------|
| Connection in acc. with standard | CUL        |
| Standards/regulations            | IEC 60664  |
|                                  | EN 50178   |
|                                  | IEC 62103  |
|                                  | EN 61810-1 |
| Degree of pollution              | 3          |
| Overvoltage category             | III        |

# Single relay - REL-MR- 24DC/21HC - 2961312


## Technical data

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |


## Drawings

Drilling diagram




Basic pitch 2.5 mm

Diagram




Operating voltage range

Diagram



Interrupting rating


Diagram




Electrical service life

## Single relay - REL-MR- 24DC/21HC - 2961312

Diagram




Dimensional drawing



Service life reduction factor with various cos phi

Circuit diagram



### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.0 | 27371601 |
| eCl@ss 5.1 | 27371601 |
| eCl@ss 6.0 | 27371601 |
| eCl@ss 7.0 | 27371601 |
| eCl@ss 8.0 | 27371601 |
| eCl@ss 9.0 | 27371601 |

ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001437 |
| ETIM 3.0 | EC001437 |
| ETIM 4.0 | EC001437 |
| ETIM 5.0 | EC001437 |
| ETIM 6.0 | EC001437 |

UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11     | 39121515 |
| UNSPSC 12.01  | 39121515 |

# Single relay - REL-MR- 24DC/21HC - 2961312

## Classifications

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 39122334 |
|-------------|----------|

## Approvals

### Approvals

#### Approvals

UL Recognized / cUL Recognized / GL / EAC / EAC / UL Recognized / cUL Recognized / PRS / VDE approval of drawings / cULus Recognized

#### Ex Approvals

### Approval details

|               |                                                                                     |                                                                                                                                                       |               |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 228652 |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

|                |                                                                                     |                                                                                                                                                       |               |
|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 228652 |
|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

|    |                                                                                     |                                                                                                                                 |             |
|----|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-------------|
| GL |  | <a href="http://www.gl-group.com/newbuilding/approvals/index.html">http://www.gl-group.com/newbuilding/approvals/index.html</a> | 46016-03 HH |
|----|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-------------|

|     |                                                                                     |  |                     |
|-----|-------------------------------------------------------------------------------------|--|---------------------|
| EAC |  |  | 7500651.22.01.00244 |
|-----|-------------------------------------------------------------------------------------|--|---------------------|

|     |                                                                                     |  |               |
|-----|-------------------------------------------------------------------------------------|--|---------------|
| EAC |  |  | EAC-Zulassung |
|-----|-------------------------------------------------------------------------------------|--|---------------|

|               |                                                                                     |                                                                                                                                                       |               |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 228652 |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

|                |                                                                                     |                                                                                                                                                       |               |
|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 228652 |
|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

## Single relay - REL-MR- 24DC/21HC - 2961312

### Approvals

|     |                                                                                   |                                                     |                   |
|-----|-----------------------------------------------------------------------------------|-----------------------------------------------------|-------------------|
| PRS |  | <a href="http://www.prs.pl/">http://www.prs.pl/</a> | TE/2109/880590/16 |
|-----|-----------------------------------------------------------------------------------|-----------------------------------------------------|-------------------|

|                          |                                                                                   |                                                                                                                                                                                                         |          |
|--------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE approval of drawings |  | <a href="http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx">http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx</a> | 40007758 |
|--------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|

|                  |                                                                                   |                                                                                                                                                       |  |
|------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| cULus Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> |  |
|------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--|

### Accessories

#### Additional products

##### Relay socket - PLC-BSP- 24DC/21HC - 2912345



14 mm PLC basic terminal block for high continuous currents with spring-cage connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 24 V DC

##### Relay socket - PLC-BSP- 24UC/21HC - 2912358



14 mm PLC basic terminal block for high continuous currents with spring-cage connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 24 V AC/DC

##### Relay socket - PLC-BSP- 48DC/21HC - 2912361



14 mm PLC basic terminal block for high continuous currents with spring-cage connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 48 V DC

## Single relay - REL-MR- 24DC/21HC - 2961312

### Accessories

#### Relay socket - PLC-BSC- 24DC/21HC - 2967772



14 mm PLC basic terminal block for high continuous currents with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 24 V DC

---

#### Relay socket - PLC-BSC- 24UC/21HC - 2967785



14 mm PLC basic terminal block for high continuous currents with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 24 V AC/DC

---

#### Relay socket - PLC-BSC- 48DC/21HC - 2967798



14 mm PLC basic terminal block for high continuous currents with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 48 V DC

---

#### Relay socket - PLC-BPT- 24DC/21HC - 2900254



14 mm PLC basic terminal block for high continuous currents with push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 24 V DC

---

#### Relay socket - PLC-BPT- 24UC/21HC - 2900255



14 mm PLC basic terminal block for high continuous currents with push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 24 V AC/DC

---

## Single relay - REL-MR- 24DC/21HC - 2961312

### Accessories

Relay socket - PLC-BPT- 48DC/21HC - 2900256



14 mm PLC basic terminal block for high continuous currents with push-in connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, 1 PDT, input voltage 48 V DC

---

Relay socket - PR1-BSC2/2X21 - 2833518



Relay socket PR1..., for miniature power relay or miniature switching relay with 1 or 2 PDT or solid-state relay of same construction, 2/2 level design, screw connections, connection facility for input/interference suppression modules

---

Relay socket - PR1-BSC3/2X21 - 2833521



Relay socket PR1..., for miniature power relay or miniature switching relay with 1 or 2 PDT or solid-state relay of same construction, 1/3 level design, screw connections, connection facility for input/interference suppression modules

---

Relay socket - PR1-BSP3/2X21 - 2833534



Relay socket PR1..., for miniature power relay or miniature switching relay with 1 or 2 PDT or solid-state relay of same construction, 1/3 level design, spring-cage connections, connection facility for input/interference suppression modules

---

Relay socket - RIF-1-BPT/2X21 - 2900931



RIF-1... relay base, for miniature power relay with 1 or 2 PDTs or solid-state relays of the same design, push-in connection, plug-in option for input/suppressor modules, for mounting on NS 35/7,5