



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)**

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



# **FDS4935BZ**

## **Dual 30 Volt P-Channel PowerTrench® MOSFET**

### **General Description**

This P-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers, and battery chargers.



These MOSFETs feature faster switching and lower gate charge than other MOSFETs with comparable  $R_{DS(ON)}$  specifications.

The result is a MOSFET that is easy and safer to drive (even at very high frequencies), and DC/DC power supply designs with higher overall efficiency.



### **Features**

- -6.9 A, -30 V.  $R_{DS(ON)} = 22 \text{ m}\Omega @ V_{GS} = -10 \text{ V}$   
 $R_{DS(ON)} = 35 \text{ m}\Omega @ V_{GS} = -4.5 \text{ V}$
- Extended  $V_{GSS}$  range (-25V) for battery applications
- ESD protection diode (note 3)
- High performance trench technology for extremely low  $R_{DS(ON)}$
- High power and current handling capability



### **Absolute Maximum Ratings**

$T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol         | Parameter                                                                  | Ratings     | Units            |
|----------------|----------------------------------------------------------------------------|-------------|------------------|
| $V_{DS}$       | Drain-Source Voltage                                                       | -30         | V                |
| $V_{GS}$       | Gate-Source Voltage                                                        | $\pm 25$    | V                |
| $I_D$          | Drain Current – Continuous (Note 1a)                                       | -6.9        | A                |
|                | – Pulsed                                                                   | -50         |                  |
| $P_D$          | Power Dissipation for Single Operation (Note 1a)<br>(Note 1b)<br>(Note 1c) | 1.6         | W                |
|                |                                                                            | 1.0         |                  |
|                |                                                                            | 0.9         |                  |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range                           | -55 to +150 | $^\circ\text{C}$ |

### **Thermal Characteristics**

|                 |                                                   |    |                    |
|-----------------|---------------------------------------------------|----|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient (Note 1a) | 78 | $^\circ\text{C/W}$ |
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case (Note 1)     | 40 | $^\circ\text{C/W}$ |

### **Package Marking and Ordering Information**

| Device Marking | Device    | Reel Size | Tape width | Quantity   |
|----------------|-----------|-----------|------------|------------|
| FDS4935BZ      | FDS4935BZ | 13"       | 12mm       | 2500 units |

**Electrical Characteristics** $T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

**Off Characteristics**

|                                      |                                           |                                                                    |     |    |          |                      |
|--------------------------------------|-------------------------------------------|--------------------------------------------------------------------|-----|----|----------|----------------------|
| $BV_{DSS}$                           | Drain–Source Breakdown Voltage            | $V_{GS} = 0\text{ V}, I_D = -250\text{ }\mu\text{A}$               | -30 |    |          | V                    |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | Breakdown Voltage Temperature Coefficient | $I_D = -250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$ |     | 24 |          | mV/ $^\circ\text{C}$ |
| $I_{DSS}$                            | Zero Gate Voltage Drain Current           | $V_{DS} = -24\text{ V}, V_{GS} = 0\text{ V}$                       |     |    | -1       | $\mu\text{A}$        |
| $I_{GSS}$                            | Gate–Body Leakage                         | $V_{GS} = \pm 25\text{ V}, V_{DS} = 0\text{ V}$                    |     |    | $\pm 10$ | $\mu\text{A}$        |

**On Characteristics** (Note 2)

|                                        |                                                |                                                                                                                                                                        |    |                  |                |                      |
|----------------------------------------|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------------------|----------------|----------------------|
| $V_{GS(th)}$                           | Gate Threshold Voltage                         | $V_{DS} = V_{GS}, I_D = -250\text{ }\mu\text{A}$                                                                                                                       | -1 | -1.9             | -3             | V                    |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$ | Gate Threshold Voltage Temperature Coefficient | $I_D = -250\text{ }\mu\text{A}$ , Referenced to $25^\circ\text{C}$                                                                                                     |    | -5               |                | mV/ $^\circ\text{C}$ |
| $r_{DS(on)}$                           | Static Drain–Source On–Resistance              | $V_{GS} = -10\text{ V}, I_D = -6.9\text{ A}$<br>$V_{GS} = -4.5\text{ V}, I_D = -5.3\text{ A}$<br>$V_{GS} = -10\text{ V}, I_D = -6.9\text{ A}, T_J = 125^\circ\text{C}$ |    | 18<br>27.5<br>26 | 22<br>35<br>34 | m $\Omega$           |
| $g_{FS}$                               | Forward Transconductance                       | $V_{DS} = -5\text{ V}, I_D = -6.9\text{ A}$                                                                                                                            |    | 22               |                | S                    |

**Dynamic Characteristics**

|           |                              |                                                                       |  |      |  |    |
|-----------|------------------------------|-----------------------------------------------------------------------|--|------|--|----|
| $C_{iss}$ | Input Capacitance            | $V_{DS} = -15\text{ V}, V_{GS} = 0\text{ V},$<br>$f = 1.0\text{ MHz}$ |  | 1360 |  | pF |
| $C_{oss}$ | Output Capacitance           |                                                                       |  | 240  |  | pF |
| $C_{rss}$ | Reverse Transfer Capacitance |                                                                       |  | 200  |  | pF |

**Switching Characteristics** (Note 2)


|              |                                           |                                                                                                   |  |    |     |    |
|--------------|-------------------------------------------|---------------------------------------------------------------------------------------------------|--|----|-----|----|
| $t_{d(on)}$  | Turn–On Delay Time                        | $V_{DD} = -15\text{ V}, I_D = -1\text{ A},$<br>$V_{GS} = -10\text{ V}, R_{GEN} = 6\text{ }\Omega$ |  | 12 | 22  | ns |
| $t_r$        | Turn–On Rise Time                         |                                                                                                   |  | 13 | 23  | ns |
| $t_{d(off)}$ | Turn–Off Delay Time                       |                                                                                                   |  | 68 | 108 | ns |
| $t_f$        | Turn–Off Fall Time                        |                                                                                                   |  | 38 | 61  | ns |
| $Q_{g(TOT)}$ | Total Gate Charge, $V_{GS} = 10\text{ V}$ | $V_{DS} = -15\text{ V}, I_D = -6.9\text{ A},$<br>$V_{GS} = -10\text{ V}$                          |  | 29 | 40  | nC |
| $Q_{g(TOT)}$ | Total Gate Charge, $V_{GS} = 5\text{ V}$  |                                                                                                   |  | 16 | 23  | nC |
| $Q_{gs}$     | Gate–Source Charge                        |                                                                                                   |  | 4  |     | nC |
| $Q_{gd}$     | Gate–Drain Charge                         |                                                                                                   |  | 7  |     | nC |

**Drain–Source Diode Characteristics and Maximum Ratings**


|                 |                                                       |                                                                                 |  |      |      |    |
|-----------------|-------------------------------------------------------|---------------------------------------------------------------------------------|--|------|------|----|
| I <sub>S</sub>  | Maximum Continuous Drain–Source Diode Forward Current |                                                                                 |  |      | –2.1 | A  |
| V <sub>SD</sub> | Drain–Source Diode Forward Voltage                    | V <sub>GS</sub> = 0 V, I <sub>S</sub> = –2.1 A (Note 2)                         |  | –0.8 | –1.2 | V  |
| t <sub>RR</sub> | Reverse Recovery Time                                 | I <sub>F</sub> = –8.8 A,<br>d <sub>I</sub> F/d <sub>t</sub> = 100 A/μs (Note 2) |  | 24   |      | ns |
| Q <sub>RR</sub> | Reverse Recovery Charge                               |                                                                                 |  | 9    |      | nC |

**Notes:**


1.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.



a)  $78^\circ\text{C/W}$  steady state when mounted on a  $1\text{ in}^2$  pad of 2 oz copper



b)  $125^\circ\text{C/W}$  when mounted on a  $.04\text{ in}^2$  pad of 2 oz copper



c)  $135^\circ\text{C/W}$  when mounted on a minimum pad.

Scale 1 : 1 on letter size paper

2. Pulse Test: Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2.0%

3. The diode connected between the gate and source serves only as protection against ESD. No gate overvoltage rating is implied.

# Typical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

# Typical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in Note 1c.  
Transient thermal response will change depending on the circuit board design.

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                                   |                                  |                                  |                              |                       |
|---------------------------------------------------|----------------------------------|----------------------------------|------------------------------|-----------------------|
| ACE <sup>x</sup> <sup>TM</sup>                    | FACT Quiet Series <sup>TM</sup>  | OCX <sup>TM</sup>                | SILENT SWITCHER <sup>®</sup> | UniFET <sup>TM</sup>  |
| ActiveArray <sup>TM</sup>                         | GlobalOptoisolator <sup>TM</sup> | OCXPro <sup>TM</sup>             | SMART START <sup>TM</sup>    | UltraFET <sup>®</sup> |
| Bottomless <sup>TM</sup>                          | GTO <sup>TM</sup>                | OPTOLOGIC <sup>®</sup>           | SPM <sup>TM</sup>            | VCX <sup>TM</sup>     |
| Build it Now <sup>TM</sup>                        | HiSeC <sup>TM</sup>              | OPTOPLANAR <sup>TM</sup>         | Stealth <sup>TM</sup>        | Wire <sup>TM</sup>    |
| CoolFET <sup>TM</sup>                             | I <sup>2</sup> C <sup>TM</sup>   | PACMAN <sup>TM</sup>             | SuperFET <sup>TM</sup>       |                       |
| CROSSVOLT <sup>TM</sup>                           | i-Lo <sup>TM</sup>               | POP <sup>TM</sup>                | SuperSOT <sup>TM</sup> -3    |                       |
| DOMET <sup>TM</sup>                               | ImpliedDisconnect <sup>TM</sup>  | Power247 <sup>TM</sup>           | SuperSOT <sup>TM</sup> -6    |                       |
| EcoSPARK <sup>TM</sup>                            | IntelliMAX <sup>TM</sup>         | PowerEdge <sup>TM</sup>          | SuperSOT <sup>TM</sup> -8    |                       |
| E <sup>2</sup> CMOS <sup>TM</sup>                 | ISOPLANAR <sup>TM</sup>          | PowerSaver <sup>TM</sup>         | SyncFET <sup>TM</sup>        |                       |
| EnSigna <sup>TM</sup>                             | LittleFET <sup>TM</sup>          | PowerTrench <sup>®</sup>         | TCM <sup>TM</sup>            |                       |
| FACT <sup>TM</sup>                                | MICROCOUPLER <sup>TM</sup>       | QFET <sup>®</sup>                | TinyBoost <sup>TM</sup>      |                       |
| FAST <sup>®</sup>                                 | MicroFET <sup>TM</sup>           | QS <sup>TM</sup>                 | TinyBuck <sup>TM</sup>       |                       |
| FAST <sup>r</sup> <sup>TM</sup>                   | MicroPak <sup>TM</sup>           | QT Optoelectronics <sup>TM</sup> | TinyPWM <sup>TM</sup>        |                       |
| FPS <sup>TM</sup>                                 | MICROWIRE <sup>TM</sup>          | Quiet Series <sup>TM</sup>       | TinyPower <sup>TM</sup>      |                       |
| FRFET <sup>TM</sup>                               | MSX <sup>TM</sup>                | RapidConfigure <sup>TM</sup>     | TinyLogic <sup>®</sup>       |                       |
|                                                   | MSXPro <sup>TM</sup>             | RapidConnect <sup>TM</sup>       | TINYOPTO <sup>TM</sup>       |                       |
| Across the board. Around the world. <sup>TM</sup> |                                  | μSerDes <sup>TM</sup>            | TruTranslation <sup>TM</sup> |                       |
| The Power Franchise <sup>®</sup>                  |                                  | ScalarPump <sup>TM</sup>         | UHC <sup>TM</sup>            |                       |
| Programmable Active Droop <sup>TM</sup>           |                                  |                                  |                              |                       |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                   |
|--------------------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                           |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                          |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative