

Safety isolating transformer RKD 30/2x12



Picture shows RKD 60 2x12

Advantages

Minimum size at high power
Low weight
Dual input and dual output voltage for series or parallel connection
Minimal no-load losses
Outstanding temperature behaviour thanks to low magnetic leakage field
Very low noise field


Applications

As a mains transformer for adjustment of the voltage and simple electrical isolation.

As an isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Safety isolating transformer
to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6,
UL 5085-1/-2, CSA 22.2 No.66

Approvals



UL 5085-1/-2, CSA 22.2 No.66



Safety isolating transformer RKD 30/2x12

Electrical data	Type	RKD 30/2x12
	Input	
	Rated input voltage	2 x 115 Vac
	Rated frequency	50 - 60 Hz
	Output	
	Rated output voltage	2 x 12 Vac
	Rated Power	30 VA
	No-load voltage (app. x factor)	1.20
	No-load loss (typ.)	0.45 W
	Efficiency	80.0 %
	Standards	
	Classification	Safety isolating transformer
	Approvals	
	Approvals	cURus
	Environment	
	Ambient temperature max.	40 °C
	Safety and protection	
	Type	Open type
	Insulation class	VDE=B, UL=class 105
	Protection index	IP 00
	Safety class (prepared)	II
	Short circuit strength	non-short-circuit proof
	Test voltage	4,000 Vac, 50 Hz
	Order numbers	
	Order Number	RKD 30/2x12

Mechanical data	Type	RKD 30/2x12
	Terminal and mounting	
	Fixing method	Mounting kit, M4 bolt
	Terminals	Connecting leads, 200 mm
	Measures and weights	
	Major diameter Ø	68 mm
	Outside diameter in the area of the wire lead Ø	71 mm
	Height without mounting	31 mm
	Weight	0.46 kg

Subject to change.