

LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

About Labfacility

Formed in 1971, Labfacility specialize in the field of Temperature and Process Measurement.

We are the largest UK manufacturer of both temperature sensors and thermocouple connectors

Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

Contact Details

Email
sales@labfacility.com

Website
www.labfacility.com

ANSI PVC Insulated Thermocouple Cable with Plug and Socket



Cable Description

PVC insulated flat pair construction
 Conductors laid flat PVC insulated with overall PVC sheath
 All round general purpose cable, both waterproof and very flexible
 Thermocouple extension types K & J, 2 or 5 Metre lengths available
 Conductors 7/0.2mm
 Tolerance Class 2
 Insulation rating -10°C to 105°C
 Colour code (cores & jacket) in accordance with ANSI specification

Connector Description

Ideal for general purpose use
 All contacts are polarised to ensure correct connection
 Colour coded in accordance with ANSI specification
 Maximum continuous operating temperature 220 deg°C

LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

About Labfacility

Formed in 1971, Labfacility specialize in the field of Temperature and Process Measurement.

We are the largest UK manufacturer of both temperature sensors and thermocouple connectors.

Quality & Service

Quality and Service are key elements in the continued growth of Labfacility.

Technical support is always freely available from our experienced technical sales teams and the company has ISO9001 accreditation.

Contact Details

Email
sales@labfacility.com

Website
www.labfacility.com

Type	Length	Connector	Manufactures Part No.	Farnell Order Number
K	2 metre	Miniature	EXT-K-C1-2.0-MP-MS	242-0308
K	5 metre	Miniature	EXT-K-C1-5.0-MP-MS	242-0310
K	2 metre	Standard	EXT-K-C1-2.0-SP-SS	242-0309
K	5 metre	Standard	EXT-K-C1-5.0-SP-SS	242-0311

