XS1M08MA230

inductive sensor XS1 M8 - L50mm - stainless - Sn1mm - 24..240VAC/DC - cable 2m





Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS1
Sensor design	Cylindrical M8
Size	50 mm
Body type	Fixed
Enclosure material	Stainless Steel
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	0.04 in (1 mm)
Discrete output function	1 NO
Electrical connection	Cable
Cable length	6.56 ft (2 m)
[Us] rated supply voltage	24210 V DC 24240 V AC
Switching capacity in mA	5100 mA
IP degree of protection	IP67

Complementary

M8 x 1
Frontal
Flush mountable
Stainless steel
PPS
AC/DC
2 x 0.11 mm²
PvR
<= 25 Hz AC <= 3000 Hz DC
CE
0.31 in (8 mm)
1.97 in (50 mm)
0.08 lb(US) (0.035 kg)

Environment

Product certifications	CSA CCC UL
Ambient air temperature for operation	-13176 °F (-2580 °C)

Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	00785901910336
Nbr. of units in pkg.	1
Package weight(Lbs)	0.13 lb(US) (0.06 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.83 in (2.1 cm)
Package 1 width	3.82 in (9.7 cm)
Package 1 Length	6.02 in (15.3 cm)
Package 2 Weight	2.12 oz (60 g)
Package 3 Weight	5.03 lb(US) (2.281 kg)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☐ End Of Life Information	

Contractual warranty

Warranty 18 month	ns
-------------------	----