

CAMBLOCK

5mm Pitch Low Profile Rising Clamp Terminal Blocks

- 2-12 pole double Interlocking mechanism for increased strength
- 4-12 pole solid block and end stackable
- Moulded in green UL94-V0 flame retardant PA66
- Professional rising clamp terminals
- 0.128mm²-1.23mm² (26- 16AWG) solid cable/ stranded cable
- Captive screws
-  approved

CTB0502



SPECIFICATION

Rating	10A/300V
Insulation resistance	5000M Ω /1000V
Withstand voltage	AC1500V/1min
Contact resistance	20m Ω (max)
Working temperature	-33°C to 120+°C
Mouldings	UL94-V0 flame retardant PA66
Screw/torque	M2.5 steel, nickel plated 0.4Nm
Recommended PCB hole size	ϕ 1.4mm

PCB
TERMINAL
BLOCKS

TYPE NO.	POLES	LENGTH
CTB0502/2	2	10mm
CTB0502/3	3	15mm
CTB0502/4	4	20mm
CTB0502/5	5	25mm
CTB0502/6	6	30mm
CTB0502/7	7	35mm
CTB0502/8	8	40mm
CTB0502/9	9	45mm
CTB0502/10	10	50mm
CTB0502/11	11	55mm
CTB0502/12	12	60mm

