

**OMNIMATE Signal - series BL/SL 5.08**  
**BLZP 5.08HC/03/90LR SN OR BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16


D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Female plugs with clamping-yoke connection for connecting wires with a right-angle (90° or 270°) outlet direction. The female connectors provide space for labelling and can be coded. Fastened by means of a flange or release latch. They also provide an integrated plus/minus screw, protection against faulty insertion of the wire, and they are delivered with open clamping yokes. HC = High Current.

**General ordering data**

|              |                                                                                                                               |
|--------------|-------------------------------------------------------------------------------------------------------------------------------|
| Type         | BLZP 5.08HC/03/90LR SN OR BX                                                                                                  |
| Order No.    | <a href="#">1087260000</a>                                                                                                    |
| Version      | PCB plug-in connector, female plug, 5.08 mm, No. of poles: 3, 90°, Clamping yoke connection, Clamping range, max.: 4 mm², Box |
| GTIN (EAN)   | 4032248853939                                                                                                                 |
| Qty.         | 72 pc(s).                                                                                                                     |
| Product data | IEC: 400 V / 23 A / 0.2 - 4 mm²<br>UL: 300 V / 20 A / AWG 26 - AWG 12                                                         |
| Packaging    | Box                                                                                                                           |

## OMNIMATE Signal - series BL/SL 5.08 BLZP 5.08HC/03/90LR SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

### Technical data

#### Dimensions and weights

|            |        |
|------------|--------|
| Net weight | 6.68 g |
|------------|--------|

#### System parameters

|                                              |                                     |                            |                                        |
|----------------------------------------------|-------------------------------------|----------------------------|----------------------------------------|
| Product family                               | OMNIMATE Signal - series BL/SL 5.08 | Type of connection         | Socket connector                       |
| Wire connection method                       | Clamping yoke connection            | Pitch in mm (P)            | 5.08 mm                                |
| Pitch in inches (P)                          | 0.2 inch                            | Conductor outlet direction | 90°                                    |
| No. of poles                                 | 3                                   | L1 in mm                   | 10.16 mm                               |
| L1 in inches                                 | 0.4 inch                            | Number of rows             | 1                                      |
| Pin series quantity                          | 1                                   | Rated cross-section        | 4 mm <sup>2</sup>                      |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch              | Volume resistance          | 5.00 mΩ                                |
| Can be coded                                 | Yes                                 | Stripping length           | 7 mm                                   |
| Tightening torque, min.                      | 0.4 Nm                              | Tightening torque, max.    | 0.5 Nm                                 |
| Clamping screw                               | M 2.5                               | Screwdriver blade standard | DIN 5264, ISO 8764/2-PH, ISO 8764/2-PZ |
| Plugging cycles                              | 25                                  | Packaging                  | Box                                    |

#### Material data

|                                       |          |                                       |                          |
|---------------------------------------|----------|---------------------------------------|--------------------------|
| Insulating material                   | PBT      | Colour                                | Orange                   |
| Colour chart (similar)                | RAL 2000 | Insulating material group             | IIla                     |
| CTI                                   | ≥ 200    | Insulation resistance                 | ≥ 10 <sup>8</sup> Ω      |
| UL 94 flammability rating             | V-0      | Contact material                      | Copper alloy             |
| Contact surface                       | tinned   | Layer structure of plug contact       | 4-8 μm Sn hot-dip tinned |
| Storage temperature, min.             | -25 °C   | Storage temperature, max.             | 55 °C                    |
| Max. relative humidity during storage | 80 %     | Operating temperature, min.           | -50 °C                   |
| Operating temperature, max.           | 100 °C   | Temperature range, installation, min. | -25 °C                   |
| Temperature range, installation, max. | 100 °C   |                                       |                          |

#### Conductors suitable for connection

|                                                 |                      |                                                 |                     |
|-------------------------------------------------|----------------------|-------------------------------------------------|---------------------|
| Clamping range, min.                            | 0.13 mm <sup>2</sup> | Clamping range, max.                            | 4 mm <sup>2</sup>   |
| Wire connection cross section AWG, min.         | AWG 30               | Wire connection cross section AWG, max.         | AWG 12              |
| Solid, min. H05(07) V-U                         | 0.2 mm <sup>2</sup>  | Solid, max. H05(07) V-U                         | 4 mm <sup>2</sup>   |
| Flexible, min. H05(07) V-K                      | 0.2 mm <sup>2</sup>  | Flexible, max. H05(07) V-K                      | 4 mm <sup>2</sup>   |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.2 mm <sup>2</sup>  | w. plastic collar ferrule, DIN 46228 pt 4, max. | 2.5 mm <sup>2</sup> |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.2 mm <sup>2</sup>  | w. wire end ferrule, DIN 46228 pt 1, max.       | 4 mm <sup>2</sup>   |
| Plug gauge acc. to EN 60999 a x b; Ø            | 2.8 mm x 2.4 mm      |                                                 |                     |

**OMNIMATE Signal - series BL/SL 5.08**  
**BLZP 5.08HC/03/90LR SN OR BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data**
**Rated data acc. to IEC**

|                                                                          |                   |                                                                              |       |
|--------------------------------------------------------------------------|-------------------|------------------------------------------------------------------------------|-------|
| Rated current, min. no. of poles<br>(Tu=20°C)                            | 23 A              | Rated current, max. no. of poles<br>(Tu=20°C)                                | 18 A  |
| Rated current, min. no. of poles<br>(Tu=40°C)                            | 21 A              | Rated current, max. no. of poles<br>(Tu=40°C)                                | 16 A  |
| Rated voltage for surge voltage class /<br>pollution degree II/2         | 400 V             | Rated voltage for surge voltage class /<br>pollution degree III/2            | 320 V |
| Rated voltage for surge voltage class /<br>pollution degree III/3        | 250 V             | Rated impulse voltage for surge voltage<br>class/ pollution degree II/2      | 4 kV  |
| Rated impulse voltage for surge voltage<br>class/ pollution degree III/2 | 4 kV              | Rated impulse voltage for surge voltage<br>class/ contamination degree III/3 | 4 kV  |
| Short-time withstand current resistance                                  | 3 x 1s with 120 A |                                                                              |       |

**Rated data acc. to CSA**

|                               |                                                                                   |                               |                                                                        |
|-------------------------------|-----------------------------------------------------------------------------------|-------------------------------|------------------------------------------------------------------------|
| Institute (CSA)               |  | Certificate No. (CSA)         | 200039-1121690                                                         |
| Rated voltage (Use group B)   | 300 V                                                                             | Rated voltage (Use group C)   | 50 V                                                                   |
| Rated voltage (use group D)   | 300 V                                                                             | Rated current (use group B)   | 20 A                                                                   |
| Rated current (use group D)   | 20 A                                                                              | Wire cross-section, AWG, min. | AWG 30                                                                 |
| Wire cross-section, AWG, max. | AWG 12                                                                            | Reference to approval values  | Specifications are maximum values, details - see approval certificate. |

**Rated data acc. to UL 1059**

|                               |                                                                                     |                               |        |
|-------------------------------|-------------------------------------------------------------------------------------|-------------------------------|--------|
| Institute (cURus)             |  | Certificate No. (cURus)       | E60693 |
| Rated voltage (use group B)   | 300 V                                                                               | Rated voltage (use group D)   | 300 V  |
| Rated current (use group B)   | 20 A                                                                                | Rated current (use group D)   | 10 A   |
| Wire cross-section, AWG, min. | AWG 26                                                                              | Wire cross-section, AWG, max. | AWG 12 |
| Reference to approval values  | Specifications are maximum values, details - see approval certificate.              |                               |        |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 4.0   | EC002637    | ETIM 5.0   | EC002637    |
| ETIM 6.0   | EC002637    | eClass 6.2 | 27-26-07-04 |
| eClass 7.1 | 27-44-04-02 | eClass 8.1 | 27-44-04-02 |
| eClass 9.0 | 27-44-04-02 | eClass 9.1 | 27-44-04-02 |

## OMNIMATE Signal - series BL/SL 5.08 BLZP 5.08HC/03/90LR SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Notes

#### Notes

- Additional colours on request
- Gold-plated contact surfaces on request
- Rated current related to rated cross-section & min. No. of poles.
- Wire end ferrule without plastic collar to DIN 46228/1
- Wire end ferrule with plastic collar to DIN 46228/4
- P on drawing = pitch
- Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.

#### IPC conformity

Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.

### Approvals

#### Approvals



#### ROHS

Conform

### Downloads

#### Approval/Certificate/Document of Conformity

[Declaration of the Manufacturer](#)

#### Brochure/Catalogue

[FL DRIVES EN](#)  
[MB DEVICE MANUF. EN](#)  
[FL DRIVES DE](#)  
[CAT 2 PORTFOLIOGUIDE EN](#)  
[FL BUILDING SAFETY EN](#)  
[FL APPL LED LIGHTING EN](#)  
[FL INDUSTR.CONTROLS EN](#)  
[FL MACHINE SAFETY EN](#)  
[FL HEATING ELECTR EN](#)  
[FL APPL INVERTER EN](#)  
[FL\\_BASE\\_STATION\\_EN](#)  
[FL ELEVATOR EN](#)  
[FL POWER SUPPLY EN](#)  
[FL 72H SAMPLE SER EN](#)  
[PO OMNIMATE EN](#)

#### Engineering Data

[EPLAN, WSCAD](#)

## OMNIMATE Signal - series BL/SL 5.08 BLZP 5.08HC/03/90LR SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Dimensional drawing

