Power Relay B

- **Pin assignment similar to ISO 7588 part 1**
- **Plug-in terminals**
- **Customized versions on request**
  - **– 24VDC versions with contact gap >0.8mm**
  - **– Integrated components (e.g. resistor, diode)**
  - **– Customized marking/color**
  - **– Special covers (e.g. notches, release features, brackets)**
  - **– Various contact arrangements and materials**

Typical applications
Cross carline up to 35A for example: rear window defogger, battery disconnection, power distribution (clamp 15)

F234_fcw1_bw

Contact Data	1 A	1 A	1 C	1 C
Contact arrangement	1 form A, 1 NO	1 form A, 1 NO	1 form C, 1 CO	1 form C, 1 CO
Rated voltage	12VDC	24VDC	12VDC	24VDC
Limiting continuous current form A/form B (NO/NC)				
23°C	50A	50A	50/35A	50/35A
85°C	35A	35A	35/25A	35/25A
125°C	15A	15A	15/10A	15/10A
Limiting making current[1] A/B (NO/NC)	120A	120A	120/45A	120/45A
Limiting breaking current, A/B (NO/NC)	30A	20A	30/20A	20/10A
Limiting short-time current overload current, ISO 8820-3[2]	1.35 x 35A, 1800s 2.00 x 35A, 5s 3.50 x 35A, 0.5s 6.00 x 35A, 0.1s			
Jump start test, ISO 16750-1	24VDC for 5min, conducting nominal current at 23°C			
Contact material	Silver based			
Min. recommended contact load[3]	1A at 5VDC			
Initial voltage drop, at 10A, typ./max.				
form A (NO)	15/200mV	15/200mV	15/200mV	15/200mV
form B (NC)	-	-	20/250mV	20/250mV
Frequency of operation, at nominal load	6 ops./min (0.1Hz)			
Operate/release time typ.	7/2ms[4]			
Electrical endurance, ops.				
resistive load, A (NO)	>2.5x10^5 30A, 14VDC	>2.5x10^5 20A, 28VDC	>2.5x10^5 30A, 14VDC	>2.5x10^5 20A, 28VDC
resistive load, B (NC)	-	-	>1x10^5 20A, 14VDC	>2.5x10^5 10A, 28VDC
Mechanical endurance	1x10^6 ops.			

1) The values apply to a resistive or inductive load with suitable spark suppression and at maximum 14VDC for 12VDC or 28VDC for 24VDC load voltages. For a load current duration of maximum 3s for a make/break ratio of 1:10.
2) Current and time are compatible with circuit protection by a typical automotive fuse. Relay will make, carry and break the specified current.
3) See chapter Diagnostics of Relays in our Application Notes or consult the internet at http://relays.te.com/appnotes/
4) For unsuppressed relay coil. A low resistive suppression device in parallel to the relay coil increases the release time and reduces the lifetime caused by increased erosion and/or higher risk of contact tack welding.

Coil Data	
Rated coil voltage	12/24VDC

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance[5] Ω±10%	Rated coil power[5] W
001	12	8	1.5	85	1.7
002	12	6.5	1	75	1.9
004	24	16	3	255	2.3

5) Without components in parallel.
All figures are given for coil without pre-energization, at ambient temperature +23°C.

Insulation Data	
Initial dielectric strength	
between open contacts	500V$_{rms}$
between contact and coil	500V$_{rms}$
between adjacent contacts	500V$_{rms}$
Load dump test	
ISO 7637-1 (12VDC), test pulse 5	V_s=+86.5VDC
ISO 7637-2 (24VDC), test pulse 5	V_s=+200VDC

Other Data	
EU RoHS/ELV compliance	compliant
Protection to heat and fire according UL94	HB or better[6]
Ambient temperature	-40 to 125°C
Climatic cycling with condensation, EN ISO 6988	6 cycles, storage 8/16h
Temperature cycling, IEC 60068-2-14, Nb	10 cycles, -40/+85°C (5°C/min)
Damp heat cyclic, IEC 60068-2-30, Db, Variant 1	6 cycles, upper air temp. 55°C
Damp heat constant, IEC 60068-2-3, Ca	56 days
Category of environmental protection, IEC 61810	RT I – dustproof
Degree of protection, IEC 60529	IP54
Corrosive gas	
IEC 60068-2-42	10±2cm^3/m^3 SO_2, 10 days
IEC 60068-2-43	1±0.3cm^3/m^3 H_2S, 10 days
Vibration resistance (functional)	
IEC 60068-2-6 (sine sweep)	10 to 500Hz, min. 5g[7]
Shock resistance (functional)	
IEC 60068-2-27 (half sine)	11ms, min. 20g[7]
Drop test, free fall, IEC 60068-2-32	1m onto concrete

02-2017, Rev. 0217
www.te.com
© 2017 TE Connectivity.

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Power Relay B (Continued)

Other Data (continued)	
Terminal type	plug-in, QC
Cover retention	
pull force	200N
push force	200N
Terminal retention	
pull force	100N
push force	100N
resistance to bending[8)]	10N
force applied to side[8)]	10N
torque	0.3Nm
Weight	approx. 35g (1.2oz)
Packaging unit	200 pcs.

6) Refers to used mateials.
7) No change in the switching state >10µs. Valid for NC contacts, NO contact values significantly higher.
8) Values apply 2mm from the end of the terminal. When the force is removed, the terminal must not have moved by more than 0.3mm.

Accessories	
For details see datasheet	Connectors for Mini ISO Relays

Terminal Assignment

NO
1 form A, NO



NOR
1 form A, NO with resistor



NO_2x87
1 form A, 1 NO (2x87)



NOR_2x87
1 form A, 1 NO (2x87) with resistor



NOD_2x87
1 form A, 1 NO (2x87) with diode



CO
1 form C, CO



COR
1 form C, CO with resistor



COD
1 form C, CO with diode



02-2017, Rev. 0217
www.te.com
© 2017 TE Connectivity.

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Power Relay B (Continued)

Dimensions

Power Relay B with bracket



Power Relay B without bracket



View of the terminals (bottom view)

1 form C
1 form A is without 87a



1 form A (2x87)



1 form A non ISO
(Terminals 30 and 86 changed position)



02-2017, Rev. 0217
www.te.com
© 2017 TE Connectivity.

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Power Relay B (Continued)

Product code structure

Typical product code: **V23234** **-A** **0** **001** **-X040**

Type
V23234 Power Relay B

Contact arrangement
A 1 form C, 1 CO
B 1 form A, 1 NO
C 1 form A, 1 NO (2x87)
K 1 form A, 1 NO (non ISO)

Cover
0 Standard
1 Bracket near terminal 30 ISO

Coil
001 12VDC
002 12VDC
004 24VDC

Terminal/arrangement
Xnnn Customized (nnn: version number)

Product code	Arrangement	Cover	Coil suppr.	Circuit[1)]	Coil	Contact mat.	Terminals	Part number
V23234-A0001-X032	1 form C,	Standard	Resistor 680Ω	COR	12VDC	Silver based	Plug-in, QC	1-1904020-2
V23234-A0001-X038	1 CO		Diode (cathode 86)	COD				1-1904020-5
V23234-A0001-X040				CO				4-1904020-7
V23234-A0004-X055					24VDC			2-1904025-6
V23234-A0004-X051			Diode (cathode 86)	COD				2-1904025-3
V23234-A0004-X053			Resistor 1400Ω	COR				2-1904025-5
V23234-A1001-X033		Bracket	Resistor 680Ω		12VDC			1-1904022-1
V23234-A1001-X036				CO				3-1904022-2
V23234-A1001-X041			Diode (cathode 86)	COD				2-1904022-3
V23234-A1004-X050				CO	24VDC			1-1904027-1
V23234-A1004-X054			Resistor 1400Ω	COR				3-1904027-2
V23234-A1004-X094			Diode (cathode 86)	COD				4-1904099-3
V23234-B0001-X001	1 form A,	Standard	Resistor 680Ω	NOR	12VDC			5-1904006-1
V23234-B0002-X012	1 NO			NO				1-1904008-2
V23234-B1001-X004		Bracket	Resistor 680Ω	NOR				1-1904007-1
V23234-B1001-X010				NO				1-1904007-2
V23234-C0001-X003	1 form A,	Standard	Diode (cathode 86)	NOD_2x87				2-1904011-1
V23234-C0001-X006	1 NO (2x87)			NO_2x87				2-1904011-2
V23234-C0004-X018			Resistor 1400Ω	NOR_2x87	24VDC			2-1904015-1
V23234-C0004-X020				NO_2x87				1-1904015-3
V23234-C1001-X005		Bracket			12VDC			5-1904012-1
V23234-C1004-X017					24VDC			5-1904014-1
V23234-C1004-X085			Resistor 1400Ω	NOR_2x87				1904015-5
V23234-K1001-X024	1 form A, 1 NO		Resistor 680Ω	NOR (non ISO)	12VDC		Plug-in, QC /non ISO	5-1904018-1

1) See terminal assignment diagrams.

Other types on request.

This list represents the most common types and does not show all variants covered by this datasheet.

02-2017, Rev. 0217
www.te.com
© 2017 TE Connectivity.

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.