


# "18650" LITHIUM-ION BATTERY HOLDERS



**NOTE:** PC Mount Battery Clip Available See Page 9.

## "18650" CELL



### FEATURES

- Low profile surface mount holder for Cylindrical Lithium and alkaline batteries
- UL 94V-0 heat resistant nylon housing well suited for reflow soldering
- Battery installation and removal does not require tools

- Securely holds battery in place
- Polarity clearly marked for orientation
- Accommodates cells with or without built-in PCB protection circuits

**Operating Temp Range:**  
-60°F to +290°F (-50°C to +145°C)


### APPLICATIONS

- Computer memory, power backup systems
- Digital readers
- Laptop and touch pad computers
- PLC and industrial controls

## THRU HOLE MOUNT

## SURFACE MOUNT


### SINGLE CELL



### SPECIFICATIONS

**Base:** High Temp Nylon 46, UL 94V-0  
**Contacts:** .012 (.30) Phosphor Bronze, Tin-Nickel Plate

**CAT. NO. 1043**




### SPECIFICATIONS

**Base:** High Temp Nylon 46, UL 94V-0  
**Contacts:** .012 (.30) Phosphor Bronze, Gold Plate (Flash)

**CAT. NO. 1042**


### DUAL CELL



### SPECIFICATIONS

**Base:** High Temp Nylon 46, UL 94V-0  
**Contacts:** .012 (.30) Phosphor Bronze, Tin-Nickel Plate

**CAT. NO. 1049**



### SPECIFICATIONS

**Base:** High Temp Nylon 46, UL 94V-0  
**Contacts:** .012 (.30) Phosphor Bronze, Gold Plate (Flash)

**CAT. NO. 1048**