

Modular Terminal Blocks with Fixing Flange or Snap-In Mounting Foot 1.5 mm² 260 Series

0.08 ... 1.5 mm ² 400 V/6 kV/3 ① I _N 18 A	AWG 28 ... 16 300 V, 10 A ② 300 V, 15 A ③	0.08 ... 1.5 mm ² 400 V/6 kV/3 ① I _N 18 A	AWG 28 ... 16 300 V, 10 A ② 300 V, 15 A ③
Terminal block width 5 mm / 0.197 in.  8 ... 9 mm / 0.33 in. ②		Terminal block width 8 mm / 0.315 in.  8 ... 9 mm / 0.33 in. ②	



- ① 400 V = rated voltage
6 kV = rated surge voltage
3 = pollution degree
(also see Section 14)

- ② Strip length, see packaging or instructions.

- ③ See application notes for:
Test plug module, page 416

Color	Item No.	Pack. Unit	Color	Item No.	Pack. Unit	260 Series Accessories	
2-conductor terminal block with fixing flange, for screw or similar mounting types, fixing hole 3.2 mm Ø, with 209-123 mounting adapter also for DIN 35 rail			4-conductor terminal block with fixing flange, for screw or similar mounting types, fixing hole 3.2 mm Ø, with 209-123 mounting adapter also for DIN 35 rail			Marking accessories, see Section 13	
 gray	260-301	300 (6x50)	 gray	260-331	300 (6x50)	Aluminum carrier rail, 1000 mm long, 18 mm wide, 7 mm high  210-154 1	
 light gray	260-303	300 (6x50)	 light gray	260-333	300 (6x50)	End stop, for WSB Quick markers, for 210-154 aluminum rail, 6 mm wide  209-122 25	
 blue	260-304	300 (6x50)	 blue	260-334	300 (6x50)	Mounting foot, for DIN 35 rail, can be snapped on terminal blocks with snap-in mounting foot, 6.4 mm wide gray 209-120 25	
 orange	260-306	300 (6x50)	 orange	260-336	300 (6x50)	Mounting foot with screw, for DIN 35 rail, can be screwed on terminal blocks with fixing flange, 6.4 mm wide gray 209-123 25	
 green-yellow	260-307	300 (6x50)	 green-yellow	260-337	300 (6x50)	Mounting adapter, for DIN 35 rail, can be used as end plate, 6.5 mm wide gray 209-137 25	
2-conductor terminal block with snap-in mounting foot, for plate thickness 0.6 ... 1.2 mm, fixing hole 3.5 mm Ø, fits 210-154 aluminum rail or with 209-120 mounting adapter for DIN 35 rail			4-conductor terminal block with snap-in mounting foot, for plate thickness 0.6 ... 1.2 mm, fixing hole 3.5 mm Ø, fits 210-154 aluminum rail or with 209-120 mounting adapter for DIN 35 rail			Test plug, with 500 mm cable, 2 mm Ø red 210-136 50	
 gray	260-311	300 (6x50)	 gray	260-341	300 (6x50)	Test plug, with 500 mm cable, 2.3 mm Ø yellow 210-137 50	
 light gray	260-313	300 (6x50)	 light gray	260-343	300 (6x50)	Operating tool with partially insulated shaft, type 2, (3.5 x 0.5) mm blade  210-720 1	
 blue	260-314	300 (6x50)	 blue	260-344	300 (6x50)		
 orange	260-316	300 (6x50)	 orange	260-346	300 (6x50)		
 green-yellow	260-317	300 (6x50)	 green-yellow	260-347	300 (6x50)		
2-conductor end terminal block, without fixing foot, for terminal strips with snap-in mounting feet			4-conductor end terminal block, without fixing foot, for terminal strips with snap-in mounting feet				
 gray	260-321	300 (6x50)	 gray	260-351	300 (6x50)		
 light gray	260-323	300 (6x50)	 light gray	260-353	300 (6x50)		
 blue	260-324	300 (6x50)	 blue	260-354	300 (6x50)		
 orange	260-326	300 (6x50)	 orange	260-356	300 (6x50)		
 green-yellow	260-327	300 (6x50)	 green-yellow	260-357	300 (6x50)		
Item-Specific Accessories			Item-Specific Accessories				
Test plug module,  can be snapped together, 5 mm wide gray 249-135 100 (4x25)			Test plug module,  can be snapped together, 8 mm wide gray 249-138 100 (4x25)				
Test plug module with locking levers,  can be snapped together, 5 mm wide gray 260-404 100 (4x25)			Test plug module with locking levers,  can be snapped together, 8 mm wide gray 260-405 100 (4x25)				
260 Series Accessories							
For marking accessories, see Section 13							
End plate with fixing flange  gray 260-361 300 (6x50)			Comb-style jumper bar, insulated, I _N 10 A, gray, reduces maximum conductor size to 1 mm ² /AWG 16 2-way 260-402 25				
End plate with snap-in mounting foot  gray 260-371 300 (6x50)			Operating tool, of insulating material, for inserting comb-style jumper bars 2-way 209-132 1				