

Thyristor \ Diode Module

$$V_{RRM} = 2 \times 1600 \text{ V}$$

$$I_{TAV} = 27 \text{ A}$$

$$V_T = 1.27 \text{ V}$$

Phase leg

Part number

MCD26-16io1B



Backside: isolated

 E72873



Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability
- Direct Copper Bonded Al₂O₃-ceramic

Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: TO-240AA

- Isolation Voltage: 3600 V~
- Industry standard outline
- RoHS compliant
- Soldering pins for PCB mounting
- Base plate: DCB ceramic
- Reduced weight
- Advanced power cycling

Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Rectifier				Ratings			
Symbol	Definition	Conditions		min.	typ.	max.	Unit
$V_{RSM/DSM}$	max. non-repetitive reverse/forward blocking voltage	$T_{VJ} = 25^{\circ}\text{C}$				1700	V
$V_{RRM/DRM}$	max. repetitive reverse/forward blocking voltage	$T_{VJ} = 25^{\circ}\text{C}$				1600	V
$I_{R/D}$	reverse current, drain current	$V_{R/D} = 1600\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$			100	μA
		$V_{R/D} = 1600\text{ V}$	$T_{VJ} = 125^{\circ}\text{C}$			3	mA
V_T	forward voltage drop	$I_T = 40\text{ A}$	$T_{VJ} = 25^{\circ}\text{C}$			1.27	V
		$I_T = 80\text{ A}$				1.64	V
		$I_T = 40\text{ A}$	$T_{VJ} = 125^{\circ}\text{C}$			1.27	V
		$I_T = 80\text{ A}$				1.65	V
I_{TAV}	average forward current	$T_C = 85^{\circ}\text{C}$	$T_{VJ} = 125^{\circ}\text{C}$			27	A
$I_{T(RMS)}$	RMS forward current	180° sine				42	A
V_{T0}	threshold voltage	} for power loss calculation only	$T_{VJ} = 125^{\circ}\text{C}$			0.85	V
r_T	slope resistance					11	m Ω
R_{thJC}	thermal resistance junction to case					0.88	K/W
R_{thCH}	thermal resistance case to heatsink				0.2		K/W
P_{tot}	total power dissipation		$T_C = 25^{\circ}\text{C}$			115	W
I_{TSM}	max. forward surge current	$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 45^{\circ}\text{C}$			520	A
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			560	A
		$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 125^{\circ}\text{C}$			440	A
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			475	A
I^2t	value for fusing	$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 45^{\circ}\text{C}$			1.35	kA ² s
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			1.31	kA ² s
		$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 125^{\circ}\text{C}$			970	A ² s
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			940	A ² s
C_J	junction capacitance	$V_R = 400\text{ V}$ $f = 1\text{ MHz}$	$T_{VJ} = 25^{\circ}\text{C}$		22		pF
P_{GM}	max. gate power dissipation	$t_p = 30\text{ }\mu\text{s}$	$T_C = 125^{\circ}\text{C}$			10	W
		$t_p = 300\text{ }\mu\text{s}$				5	W
P_{GAV}	average gate power dissipation					0.5	W
$(di/dt)_{cr}$	critical rate of rise of current	$T_{VJ} = 125^{\circ}\text{C}; f = 50\text{ Hz}$ repetitive, $I_T = 45\text{ A}$				150	A/ μs
		$t_p = 200\text{ }\mu\text{s}; di_G/dt = 0.45\text{ A}/\mu\text{s};$ $I_G = 0.45\text{ A}; V = \frac{2}{3} V_{DRM}$ non-repet., $I_T = 27\text{ A}$				500	A/ μs
$(dv/dt)_{cr}$	critical rate of rise of voltage	$V = \frac{2}{3} V_{DRM}$	$T_{VJ} = 125^{\circ}\text{C}$			1000	V/ μs
		$R_{GK} = \infty$; method 1 (linear voltage rise)					
V_{GT}	gate trigger voltage	$V_D = 6\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$			1.5	V
			$T_{VJ} = -40^{\circ}\text{C}$			1.6	V
I_{GT}	gate trigger current	$V_D = 6\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$			100	mA
			$T_{VJ} = -40^{\circ}\text{C}$			200	mA
V_{GD}	gate non-trigger voltage	$V_D = \frac{2}{3} V_{DRM}$	$T_{VJ} = 125^{\circ}\text{C}$			0.2	V
I_{GD}	gate non-trigger current					10	mA
I_L	latching current	$t_p = 10\text{ }\mu\text{s}$	$T_{VJ} = 25^{\circ}\text{C}$			450	mA
		$I_G = 0.45\text{ A}; di_G/dt = 0.45\text{ A}/\mu\text{s}$					
I_H	holding current	$V_D = 6\text{ V}$ $R_{GK} = \infty$	$T_{VJ} = 25^{\circ}\text{C}$			200	mA
t_{gd}	gate controlled delay time	$V_D = \frac{1}{2} V_{DRM}$	$T_{VJ} = 25^{\circ}\text{C}$			2	μs
		$I_G = 0.45\text{ A}; di_G/dt = 0.45\text{ A}/\mu\text{s}$					
t_q	turn-off time	$V_R = 100\text{ V}; I_T = 20\text{ A}; V = \frac{2}{3} V_{DRM}$ $T_{VJ} = 100^{\circ}\text{C}$ $di/dt = 10\text{ A}/\mu\text{s}$ $dv/dt = 20\text{ V}/\mu\text{s}$ $t_p = 200\text{ }\mu\text{s}$			150		μs

Package TO-240AA				Ratings				
Symbol	Definition	Conditions		min.	typ.	max.	Unit	
I _{RMS}	RMS current	per terminal				200	A	
T _{VJ}	virtual junction temperature			-40		125	°C	
T _{op}	operation temperature			-40		100	°C	
T _{stg}	storage temperature			-40		125	°C	
Weight					81		g	
M _D	mounting torque			2.5		4	Nm	
M _T	terminal torque			2.5		4	Nm	
d _{Spp/App}	creepage distance on surface striking distance through air	terminal to terminal	13.0	9.7			mm	
d _{Spb/Apb}		terminal to backside	16.0	16.0			mm	
V _{ISOL}	isolation voltage	t = 1 second	50/60 Hz, RMS; I _{ISOL} ≤ 1 mA		3600			V
		t = 1 minute			3000			V



Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	MCD26-16io1B	MCD26-16io1B	Box	36	500955

Similar Part	Package	Voltage class
MCMA35PD1600TB	TO-240AA-1B	1600
MCMA50PD1600TB	TO-240AA-1B	1600

Equivalent Circuits for Simulation

* on die level

$T_{VJ} = 125^{\circ}\text{C}$

		Thyristor	
$V_{0\max}$	threshold voltage	0.85	V
$R_{0\max}$	slope resistance *	9.8	mΩ

Technical drawing of a 5-pin DIN connector. The drawing shows the front and side views with the following dimensions and labels:

- Overall width: 92 ± 0.5
- Distance from mounting hole to first pin: 80 ± 0.3
- Pin diameter: 6
- Pin pitch: 10
- Mounting hole diameter: $M5$
- Pin 1 diameter: 14.8
- Pin 1 to Pin 2 distance: 10 ± 0.1
- Pin 2 to Pin 3 distance: 5.5 ± 0.1
- Pin 3 to Pin 4 distance: 25 ± 0.3
- Pin 4 to Pin 5 distance: 45 ± 0.3
- Pin 5 to Pin 6 distance: 65 ± 0.3
- Pin 6 diameter: 4.4
- Pin 6 to Pin 7 distance: 20.8 ± 0.25
- Pin 7 diameter: 10 ± 0.1
- Pin 7 to Pin 8 distance: 5.5 ± 0.1
- Pin 8 diameter: 6
- Pin 8 to Pin 9 distance: 10
- Pin 9 diameter: 4.4
- Pin 9 to Pin 10 distance: 25 ± 0.3
- Pin 10 diameter: 6
- Pin 10 to Pin 11 distance: 45 ± 0.3
- Pin 11 diameter: 4.4
- Pin 11 to Pin 12 distance: 65 ± 0.3
- Pin 12 diameter: 6
- Pin 12 to Pin 13 distance: 10
- Pin 13 diameter: 4.4
- Pin 13 to Pin 14 distance: 25 ± 0.3
- Pin 14 diameter: 6
- Pin 14 to Pin 15 distance: 45 ± 0.3
- Pin 15 diameter: 4.4
- Pin 15 to Pin 16 distance: 65 ± 0.3
- Pin 16 diameter: 6
- Pin 16 to Pin 17 distance: 10
- Pin 17 diameter: 4.4
- Pin 17 to Pin 18 distance: 25 ± 0.3
- Pin 18 diameter: 6
- Pin 18 to Pin 19 distance: 45 ± 0.3
- Pin 19 diameter: 4.4
- Pin 19 to Pin 20 distance: 65 ± 0.3
- Pin 20 diameter: 6
- Pin 20 to Pin 21 distance: 10
- Pin 21 diameter: 4.4
- Pin 21 to Pin 22 distance: 25 ± 0.3
- Pin 22 diameter: 6
- Pin 22 to Pin 23 distance: 45 ± 0.3
- Pin 23 diameter: 4.4
- Pin 23 to Pin 24 distance: 65 ± 0.3
- Pin 24 diameter: 6
- Pin 24 to Pin 25 distance: 10
- Pin 25 diameter: 4.4
- Pin 25 to Pin 26 distance: 25 ± 0.3
- Pin 26 diameter: 6
- Pin 26 to Pin 27 distance: 45 ± 0.3
- Pin 27 diameter: 4.4
- Pin 27 to Pin 28 distance: 65 ± 0.3
- Pin 28 diameter: 6
- Pin 28 to Pin 29 distance: 10
- Pin 29 diameter: 4.4
- Pin 29 to Pin 30 distance: 25 ± 0.3
- Pin 30 diameter: 6
- Pin 30 to Pin 31 distance: 45 ± 0.3
- Pin 31 diameter: 4.4
- Pin 31 to Pin 32 distance: 65 ± 0.3
- Pin 32 diameter: 6
- Pin 32 to Pin 33 distance: 10
- Pin 33 diameter: 4.4
- Pin 33 to Pin 34 distance: 25 ± 0.3
- Pin 34 diameter: 6
- Pin 34 to Pin 35 distance: 45 ± 0.3
- Pin 35 diameter: 4.4
- Pin 35 to Pin 36 distance: 65 ± 0.3
- Pin 36 diameter: 6
- Pin 36 to Pin 37 distance: 10
- Pin 37 diameter: 4.4
- Pin 37 to Pin 38 distance: 25 ± 0.3
- Pin 38 diameter: 6
- Pin 38 to Pin 39 distance: 45 ± 0.3
- Pin 39 diameter: 4.4
- Pin 39 to Pin 40 distance: 65 ± 0.3
- Pin 40 diameter: 6
- Pin 40 to Pin 41 distance: 10
- Pin 41 diameter: 4.4
- Pin 41 to Pin 42 distance: 25 ± 0.3
- Pin 42 diameter: 6
- Pin 42 to Pin 43 distance: 45 ± 0.3
- Pin 43 diameter: 4.4
- Pin 43 to Pin 44 distance: 65 ± 0.3
- Pin 44 diameter: 6
- Pin 44 to Pin 45 distance: 10
- Pin 45 diameter: 4.4
- Pin 45 to Pin 46 distance: 25 ± 0.3
- Pin 46 diameter: 6
- Pin 46 to Pin 47 distance: 45 ± 0.3
- Pin 47 diameter: 4.4
- Pin 47 to Pin 48 distance: 65 ± 0.3
- Pin 48 diameter: 6
- Pin 48 to Pin 49 distance: 10
- Pin 49 diameter: 4.4
- Pin 49 to Pin 50 distance: 25 ± 0.3
- Pin 50 diameter: 6
- Pin 50 to Pin 51 distance: 45 ± 0.3
- Pin 51 diameter: 4.4
- Pin 51 to Pin 52 distance: 65 ± 0.3
- Pin 52 diameter: 6
- Pin 52 to Pin 53 distance: 10
- Pin 53 diameter: 4.4
- Pin 53 to Pin 54 distance: 25 ± 0.3
- Pin 54 diameter: 6
- Pin 54 to Pin 55 distance: 45 ± 0.3
- Pin 55 diameter: 4.4
- Pin 55 to Pin 56 distance: 65 ± 0.3
- Pin 56 diameter: 6
- Pin 56 to Pin 57 distance: 10
- Pin 57 diameter: 4.4
- Pin 57 to Pin 58 distance: 25 ± 0.3
- Pin 58 diameter: 6
- Pin 58 to Pin 59 distance: 45 ± 0.3
- Pin 59 diameter: 4.4
- Pin 59 to Pin 60 distance: 65 ± 0.3
- Pin 60 diameter: 6
- Pin 60 to Pin 61 distance: 10
- Pin 61 diameter: 4.4
- Pin 61 to Pin 62 distance: 25 ± 0.3
- Pin 62 diameter: 6
- Pin 62 to Pin 63 distance: 45 ± 0.3
- Pin 63 diameter: 4.4
- Pin 63 to Pin 64 distance: 65 ± 0.3
- Pin 64 diameter: 6
- Pin 64 to Pin 65 distance: 10
- Pin 65 diameter: 4.4
- Pin 65 to Pin 66 distance: 25 ± 0.3
- Pin 66 diameter: 6
- Pin 66 to Pin 67 distance: 45 ± 0.3
- Pin 67 diameter: 4.4
- Pin 67 to Pin 68 distance: 65 ± 0.3
- Pin 68 diameter: 6
- Pin 68 to Pin 69 distance: 10
- Pin 69 diameter: 4.4
- Pin 69 to Pin 70 distance: 25 ± 0.3
- Pin 70 diameter: 6
- Pin 70 to Pin 71 distance: 45 ± 0.3
- Pin 71 diameter: 4.4
- Pin 71 to Pin 72 distance: 65 ± 0.3
- Pin 72 diameter: 6
- Pin 72 to Pin 73 distance: 10
- Pin 73 diameter: 4.4
- Pin 73 to Pin 74 distance: 25 ± 0.3
- Pin 74 diameter: 6
- Pin 74 to Pin 75 distance: 45 ± 0.3
- Pin 75 diameter: 4.4
- Pin 75 to Pin 76 distance: 65 ± 0.3
- Pin 76 diameter: 6
- Pin 76 to Pin 77 distance: 10
- Pin 77 diameter: 4.4
- Pin 77 to Pin 78 distance: 25 ± 0.3
- Pin 78 diameter: 6
- Pin 78 to Pin 79 distance: 45 ± 0.3
- Pin 79 diameter: 4.4
- Pin 79 to Pin 80 distance: 65 ± 0.3
- Pin 80 diameter: 6
- Pin 80 to Pin 81 distance: 10
- Pin 81 diameter: 4.4
- Pin 81 to Pin 82 distance: 25 ± 0.3
- Pin 82 diameter: 6
- Pin 82 to Pin 83 distance: 45 ± 0.3
- Pin 83 diameter: 4.4
- Pin 83 to Pin 84 distance: 65 ± 0.3
- Pin 84 diameter: 6
- Pin 84 to Pin 85 distance: 10
- Pin 85 diameter: 4.4
- Pin 85 to Pin 86 distance: $$

Keyed gate/cathode twin plugs with wire length = 350 mm, gate = white, cathode = red
Type ZY 200L (L = Left for pin pair 4/5) UL 758, style 3751




Thyristor


Fig. 1 Surge overload current I_{TSM} ,
 I_{FSM} : Crest value, t : duration




Fig. 2 I^2t versus time (1-10 ms)




Fig. 3 Max. forward current
 at case temperature



Fig. 4 Power dissipation vs. on-state current & ambient temperature
 (per thyristor or diode)



Fig. 5 Gate trigger characteristics



Fig. 6 Three phase rectifier bridge: Power dissipation versus direct
 output current and ambient temperature



Fig. 7 Gate trigger delay time


Rectifier


Fig. 8 Three phase AC-controller: Power dissipation versus RMS output current and ambient temperature




Fig. 9 Transient thermal impedance junction to case (per thyristor/diode)

R_{thJC} for various conduction angles d:

d	R_{thJC} [K/W]
DC	0.88
180°	0.92
120°	0.95
60°	0.98
30°	1.01

Constants for Z_{thJC} calculation:

i	R_{thi} [K/W]	t_i [s]
1	0.019	0.0031
2	0.029	0.0216
3	0.832	0.1910



Fig. 10 Transient thermal impedance junction to heatsink (per thyristor/diode)

R_{thJK} for various conduction angles d:

d	R_{thJK} [K/W]
DC	1.08
180°	1.12
120°	1.15
60°	1.18
30°	1.21

Constants for Z_{thJK} calculation:

i	R_{thi} [K/W]	t_i [s]
1	0.019	0.0031
2	0.029	0.0216
3	0.832	0.1910
4	0.200	0.4500